



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



**Surge protection  
SPD II 0 PV 600VDC**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Spare type 2 arrester for the SPD PV series

**General ordering data**

Order No.	<a href="#">1348520000</a>
Type	SPD II 0 PV 600VDC
Version	Surge protection, Low voltage, Spare arrester
GTIN (EAN)	4050118153019
Qty.	1 pc(s).

**Surge protection  
SPD II 0 PV 600VDC**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

Width	18 mm	Height	45 mm
Depth	58 mm	Net weight	72 g

**Temperatures**

Operating temperature	-40 °C...+70 °C	Storage temperature	-40 °C...+85 °C
-----------------------	-----------------	---------------------	-----------------

**General data**

Colour	Light Grey	Height with TS 35	74 mm
Lightning arrester	No	Optical function display	green = OK; red = arrester is defective - replace
Protection degree	IP 20	UL 94 flammability rating	V-0

**Insulation coordination acc. to EN 50178**

Pollution severity	2	Surge voltage category	III
--------------------	---	------------------------	-----

**technical data**

Max. continuous voltage, U <sub>c</sub> (DC)	550 V	Total discharge current I <sub>total</sub>	100 kA
Discharge current, max. (8/20 μs)	50 kA	Protection level U <sub>p</sub> (typ.)	≤ 2000 V
Colour	Light Grey	AC/DC/UC	DC
Response time	≤ 100 ns		

**Photovoltaic technical data**

Maximum continuous operating voltage UCPV mode +/-, -/PE, +/PE	550 V DC	Protection level U <sub>p</sub> at I <sub>n</sub> (per module)	2200 V
Protection level U <sub>p</sub> mode (+/-, -/PE, +/PE)	4000 V		

**Rated data UL**

Category	Typ 2	I <sub>max</sub>	50 kA
I <sub>n</sub>	20 kA	MCOV	600 Vdc
SCCR	200 kA	Test Voltage 39.1 (UL 1449)	600 V
UL certificate	E-File 354261 Type 2 by UL1449 Ed.3	VPR	2 kV

**Classifications**

ETIM 3.0	EC000941	UNSPSC	30-21-19-21
eClass 5.1	27-13-08-01	eClass 6.2	27-13-08-02
eClass 7.1	27-14-02-01		

**Approvals**

ROHS	Conform
------	---------

**Downloads**

Declaration of Conformity	<a href="#">K481_05_12.pdf</a>
---------------------------	--------------------------------