



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



**Part Number: 1370P**

Serial Digital Coax, RG59 Type, 20 AWG Solid BC, Foil + 85% TC Braid, CMP



## Product Description

Video Cable, RG-59 Type 20 AWG solid bare copper, foam FEP insulation, Bonded Duofoil®+85% tinned copper braid, CMP Flamarrest® jacket.

## Technical Specifications

### Product Overview

Environmental Space:	Indoor - Plenum
Suitable Applications:	Commercial Video

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Coax
20	Solid	BC - Bare Copper	0.032 in	1

Conductor Count:	1
Conductor Size:	20 AWG

#### Insulation

Material	Material Trade Name	Nominal Diameter
FFEP - Foam Fluorinated Ethylene Propylene	Teflon®	0.133 in

#### Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]
Tape	1	Aluminum/Polyester/Aluminum	Duobond® II	100 %
Braid	2	TC - Tinned Copper		85 %

#### Outer Jacket Material

Material	Material Trade Name	Nominal Diameter
PVC - Polyvinyl Chloride	Flamarrest®	0.192 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR	Outer Conductor DCR
10.1 Ohm/1000ft	4.1 Ohm/1000ft	4.1 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Shield
16.1 pF/ft

Shielding:	Multiple or Specialty
------------	-----------------------

#### Inductance

Nominal Inductance
0.097 µH/ft

#### Impedance

Nominal Characteristic Impedance
75 Ohm

#### Return Loss (RL)

Frequency [MHz]	Minimum Return (RL)
5 - 3000 MHz	15 dB

#### High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.29 dB/100ft
3.58 MHz	0.62 dB/100ft
5 MHz	0.7 dB/100ft
7 MHz	0.82 dB/100ft
10 MHz	1.05 dB/100ft
67.5 MHz	2.2 dB/100ft
71.5 MHz	2.25 dB/100ft
100 MHz	2.7 dB/100ft
135 MHz	3.2 dB/100ft
143 MHz	3.25 dB/100ft
180 MHz	3.65 dB/100ft
270 MHz	4.55 dB/100ft
360 MHz	5.25 dB/100ft
540 MHz	6.4 dB/100ft
720 MHz	7.3 dB/100ft
750 MHz	7.5 dB/100ft
1000 MHz	9.4 dB/100ft
1500 MHz	12.8 dB/100ft
2250 MHz	17.5 dB/100ft
3000 MHz	21.9 dB/100ft

#### Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.21 ns/ft	84 %

#### High Freq

Min. RL (Return Loss) [dB]
15 dB

#### Voltage

UL Voltage Rating
300 V RMS

Electrical Characteristics Notes:	Return Loss: Fixed bridge and termination
-----------------------------------	---

#### Temperature Range

UL Temp Rating:	75°C
Operating Temp Range:	0°C To +75°C

#### Mechanical Characteristics

Bulk Cable Weight:	24 lbs/1000ft
Max Recommended Pulling Tension:	37 lbs
Min Bend Radius/Minor Axis:	2 in

#### Standards

NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP
RG Type:	59/U Type
RG / Series Type:	59/U Type

#### Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes

EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU RoHS Compliance Date (yyyy-mm-dd):	2011-11-21
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	No

## Flammability, LSOH, Toxicity Testing

UL Flammability:	NFPA 262
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	Yes
---------------	-----

## Part Number

Non-Plenum Number:	1370R
--------------------	-------

## Variants

Item #	Color
1370P 0101000	Black
1370P 010500	Black
1370P 0061000	Blue, Light
1370P 006500	Blue, Light
1370P 0011000	Brown
1370P 001500	Brown
1370P 0081000	Gray
1370P 008500	Gray
1370P N3U1000	Green, Mil
1370P N3U500	Green, Mil
1370P 0031000	Orange
1370P 003500	Orange
1370P 0021000	Red
1370P 002500	Red
1370P 0071000	Violet
1370P 007500	Violet
1370P 0091000	White
1370P 009500	White
1370P 0041000	Yellow
1370P 004500	Yellow

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.