



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Honeywell Sensing and Control

Search


[narrow your search](#)

Products

- Controls Monitoring and Lighting (354)
- Machine Safety (1726)
- Sensors (7016)
- Switches (9736)

Technology

- Control and Instrumentation (1063)
- Electromechanical (9297)
- Microstructure (2298)
- Optical/Infrared (1077)
- Thick Film (1764)
- More...

Need Help?

[Click here to contact us](#)

140-103LAG-RB1 Discrete Thermistors

[\(Home : Products\)](#)


Actual product appearance may vary.

140 Series, 2,54 mm [0.1 in] disc thermistor with leads, 10,000 Ohm resistance, $\pm 10.0\%$ tolerance, 25/85 BETA = 3974

[Sales & Service](#)
[Distributor Inventory](#)
[Overview](#) | [Specs](#) | [Documentation](#) | [Application Notes](#)

Product Specifications

Availability	Global
Resistance	10,000 Ohm
Tolerance	$\pm 10.0\%$
Accuracy	25 °C [77 °F]
Beta	3974
Operating Temperature	-60 °C to 125 °C [-76 °F to 257 °F]
Diameter	2,54 mm [0.10 in]
Termination Material	Tinned copper
Lead Length	38,1 mm [1.50 in]
Time Constant in Air	10.0 s
Dissipation Constant	3,0 m/W°C
Series Name	140