



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Distributor - VS-ASI-J-Y-N-M12FS - 1404414

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



AS-Interface distributor with IP65/IP67/IP69k degree of protection for 1 flat-ribbon conductor, with a straight, A-coded, 2-pos. M12 socket

Key commercial data

| | |
|------------------------|--|
| Packing unit | 0 |
| Minimum order quantity | 1 |
| Catalog page | Page 410 (PC-2011) |
| GTIN |  4 046356 320665 |
| Custom tariff number | 85366990 |
| Country of origin | VIETNAM |

Technical data

Mechanical characteristics

| | |
|---|----------------------------|
| Number of positions | 2 |
| Connection method | AS-i penetration technique |
| Color | black |
| Tightening torque, min. | 1.65 Nm |
| Ambient temperature (operation) | -25 °C ... 75 °C |
| Ambient temperature (storage/transport) | -25 °C ... 85 °C |

Material data

| | |
|--------------------------|------------------------------|
| Housing material | PA-GF |
| Contact carrier material | TPE-U |
| Contact material | CuZn |
| Contact surface material | Ni/Au |
| Material | CuSn (M12 contact) |
| Material | TPE-U (M12 contact carrier) |
| Material | Ni/Au (M12 contact surface) |
| Cable gland material | Zinc die-cast, nickel-plated |
| Degree of protection | IP65/IP67/IP69K |

Electrical characteristics

| | |
|-----------------------|--------|
| Rated voltage (III/3) | ≤ 35 V |
|-----------------------|--------|

Distributor - VS-ASI-J-Y-N-M12FS - 1404414

Technical data

Electrical characteristics

| | |
|---------------|-------|
| Rated current | ≤ 4 A |
|---------------|-------|

Classifications

eclass

| | |
|------------|----------|
| eCl@ss 4.0 | 27140815 |
| eCl@ss 4.1 | 27140815 |
| eCl@ss 5.0 | 27143423 |
| eCl@ss 5.1 | 27143423 |
| eCl@ss 6.0 | 27143423 |
| eCl@ss 7.0 | 27449001 |

etim

| | |
|----------|----------|
| ETIM 2.0 | EC000200 |
| ETIM 3.0 | EC001856 |
| ETIM 4.0 | EC000313 |

unspsc

| | |
|---------------|----------|
| UNSPSC 6.01 | 31261501 |
| UNSPSC 7.0901 | 31261501 |
| UNSPSC 11 | 31261501 |
| UNSPSC 12.01 | 31261501 |
| UNSPSC 13.2 | 31261501 |

Accessories

Accessories

Protection and sealing elements

Screw plug - PROT-M12 - 1680539



An M12 screw plug for the unoccupied M12 sockets of the sensor/actuator cable, boxes and flush-type connectors

Sensor/Actuator cable - SAC-4P-MS/ 0,3-186/FS SCO - 1555680



Sensor/Actuator cable, 4-position, PUR, Black-gray RAL 7021, Plug straight M12-SPEEDCON, A-coded, on Socket straight M12-SPEEDCON, A-coded, Cable length: 0.3 m

Distributor - VS-ASI-J-Y-N-M12FS - 1404414

Accessories

Sensor/Actuator cable - SAC-4P-MS/ 0,5-186/FS SCO - 1555693



Sensor/Actuator cable, 4-position, PUR, Black-gray RAL 7021, Plug straight M12-SPEEDCON, A-coded, on Socket straight M12-SPEEDCON, A-coded, Cable length: 0.5 m

Sensor/Actuator cable - SAC-4P-MS/ 1,0-186/FS SCO - 1555703



Sensor/Actuator cable, 4-position, PUR, Black-gray RAL 7021, Plug straight M12-SPEEDCON, A-coded, on Socket straight M12-SPEEDCON, A-coded, Cable length: 1 m

Sensor/Actuator cable - SAC-4P-MS/ 2,0-186/FS SCO - 1555716



Sensor/Actuator cable, 4-position, PUR, Black-gray RAL 7021, Plug straight M12-SPEEDCON, A-coded, on Socket straight M12-SPEEDCON, A-coded, Cable length: 2 m

Sensor/Actuator cable - SAC-4P-MS/ 5,0-186/FS SCO - 1555729



Sensor/Actuator cable, 4-position, PUR, Black-gray RAL 7021, Plug straight M12-SPEEDCON, A-coded, on Socket straight M12-SPEEDCON, A-coded, Cable length: 5 m

Sensor/Actuator cable - SAC-4P-MS/10,0-186/FS SCO - 1555732



Sensor/Actuator cable, 4-position, PUR, Black-gray RAL 7021, Plug straight M12-SPEEDCON, A-coded, on Socket straight M12-SPEEDCON, A-coded, Cable length: 10 m

Sensor/Actuator cable - SAC-4P-MS/15,0-186/FS SCO - 1555745



Sensor/Actuator cable, 4-position, PUR, Black-gray RAL 7021, Plug straight M12-SPEEDCON, A-coded, on Socket straight M12-SPEEDCON, A-coded, Cable length: 15 m

Distributor - VS-ASI-J-Y-N-M12FS - 1404414

Accessories


Screwdriver - SZK PH2 VDE - 1205163



Screwdriver, PH crosshead, VDE insulated, size: PH 2 x 100 mm, 2-component grip, with non-slip grip

Drawings

Schematic diagram



Pin assignment M12, PIN 1: AS-i +, PIN 3: AS-i -, PIN 2,4,5: Not used

Dimensioned drawing

