

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Sercos III patch cable, shielded, star quad, 22 AWG stranded (7-wire), RAL 3020 (traffic red), RJ45 connector/IP20, straight to RJ45 connector/IP20, straight, length: 6.5 m

Sercos III patch cable



Key Commercial Data

Packing unit	1 STK
Custom tariff number	85444210
Country of origin	Poland

Technical data

Ambient conditions

Degree of protection	IP20
Compared deta	

General data

Number of positions	4
Signal type/category	Sercos III
Degree of pollution	1

Standards and Regulations

Flammability rating according to UL 94	V0

Cable

Cable type	Sercos III
Cable type (abbreviation)	93K
UL AWM style	21694 (60°C / 600 V)
Signal type/category	Sercos III CAT5 (IEC 11801), 100 Mbps
Cable structure	1x4xAWG22/7; SF/TQ



Technical data

Cable

Conductor cross section	4x 0.34 mm²	
AWG signal line	22	
Conductor structure signal line	7x 0.25 mm	
Core diameter including insulation	approx. 1.55 mm	
Wire colors	White, yellow, blue, orange	
Type of pair shielding	Aluminum-lined polyester foil	
Overall twist	Star quad	
Shielding	Tinned copper braided shield	
External sheath, color	signal red RAL 3020	
Outer sheath thickness	approx. 0.9 mm	
External cable diameter D	6.5 mm ±0.2 mm	
Minimum bending radius, fixed installation	3 x D	
Minimum bending radius, flexible installation	7 x D	
Cable weight	68 kg/km	
Outer sheath, material	PVC	
Material, inner sheath	PVC	
Material conductor insulation	PE	
Conductor material	Tin-plated Cu litz wires	
Insulation resistance	$\geq 0.5~G\Omega^*km$	
Conductor resistance	≤ 120 Ω/km	
Wave impedance	100 Ω ±15 Ω (at 100 MHz)	
Signal runtime	5.3 ns/m	
Coupling resistance	\leq 20.00 m Ω /m (at 10 Hz)	
Test voltage Core/Core	2000 V (50 Hz, 1 min.)	
Test voltage Core/Shield	2000 V (50 Hz, 1 min.)	
Flame resistance	According to UL 1685 (CSA FT 4)	
Resistance to oil	Resistant to oil to a limited extent	
Other resistance	UV resistant According to UL 1581, Section 1200	
Ambient temperature (operation)	-40 °C 70 °C (cable, fixed installation)	
	-40 °C 70 °C (cable, flexible installation)	
Ambient temperature (installation)	-20 °C 60 °C	
Ambient temperature (storage/transport)	-50 °C 70 °C	


Drawings



Cable cross section




Circuit diagram



Sercos III [93K]

Dimensional drawing





RJ45 connector, IP20

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCI@ss 5.0	27260701
eCl@ss 5.1	27060307
eCl@ss 6.0	27060390
eCl@ss 7.0	27060390
eCl@ss 8.0	27060308
eCl@ss 9.0	27060308

ETIM

ETIM 3.0	EC000830
ETIM 4.0	EC002599
ETIM 5.0	EC002599

UNSPSC

UNSPSC 6.01	26121616
UNSPSC 7.0901	26121616



Classifications

UNSPSC

UNSPSC 11	26121604
UNSPSC 12.01	31261501
UNSPSC 13.2	26121616

UNSPSC 13.2	26121616	
Approvals		
Approvals		
Approvals		
EAC		
Ex Approvals		
Approvals submitted		
Approval details		
FAC		

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com