

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Mechanical data (according to IEC 61076-2-101)		Material			
no. of poles / coding	17 / A	housing	V4A		
contact termination	crimp / socket	contact carrier	PA 66 / UL 94 VO black		
contact-∅	0.6mm	colour			
temperature range	-40 °C / +85 °C	wire	TPE		
protection class	IP 67	cross section	0.14mm ²		
mating cycles	>100	contacts / surface	CuZn / Au		
locking system	M12 STANDARD	sealing gasket	FKM		
tocking system		notting	PH 2k / III 9/ VA		


further information:

- see technical data M12-1
- see installation recommendation M16x1,5 design E



All specified data refers to the mounted M12 installation plugs \geq IP54 and requires that the connector pair be correctly plugged and locked. Influences from wires, cabels or PCB mounting are also to be faken into consideration.





article designation:

Pin Layout

pin	colour	pin	colour	pin	colour	
1	brown	7	black	13	white/green	
2	blue	8	grey	14	brown/green	
3	white	9	red	15	white/yellow	
4	green	10	purple	16	yellow/brown	
5	pink	11	grey/pink	17	white/grey	
6	yellow	12	red/blue			

SACC-E-M12FS-17CON-M16/L (see chart) VA

order-no. L (m)

						0. 0	C ()
						1405244	0,5
general tolerance acc. to DIN ISO 2768-c		эпсе 2768-с	technical changes reserved Index 1 / 2011-1		11-11-24	scale : 2:1	
	date	name	description:				
design	2011-11-24	Scheerer	·	lousing with crimp cont			
chk.				Front mounting (M16x1	,5)		page: 1
				ے			of: 1
			drawing-no.:	BA-L71RFAORX,XX (X,X	X=L)		
PHŒNIX		XIIX ACT	order-no.:	see chart			