

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Connector set - HC-KIT-B24-R02 - 1409752

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Connector set, consisting of: B24 sleeve housing and panel mounting base, 24-pos. plug and socket insert, M32 cable gland



Key Commercial Data

| Packing unit | 1 STK |
|--------------|-----------------|
| GTIN | 4 046356 752701 |
| GTIN | 4046356752701 |

Technical data

Dimensions Cable diameter

| General | | |
|----------------------------------|------------------|--|
| Number of positions | 24+PE | |
| Туре | B24 | |
| Rated voltage | 500 V | |
| Rated current | 16 A | |
| Connection method | Screw connection | |
| Cable outlet | lateral | |
| Degree of protection for housing | IP65 | |
| Connection method | Screw connection | |
| Rated voltage (III/3) | 500 V | |
| Rated surge voltage | 6 kV | |

14 mm ... 21 mm

Standards and Regulations

Rated current

| Flammability rating according to UL 94 | V0 |
|--|----|

20 A

Environmental Product Compliance



Connector set - HC-KIT-B24-R02 - 1409752

Technical data

Environmental Product Compliance

| REACh SVHC | Lead 7439-92-1 |
|------------|---|
| China RoHS | Environmentally Friendly Use Period = 50 |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Articles in set

Cable gland - G-INS-M32-M68N-NNES-S - 1411166



Cable gland, cable gland material: Nickel-plated brass, external cable diameter 15 mm ... 21 mm, shielding: no, connecting thread: M32 x 1.5, color: silver, with O-ring

Contact insert - HC-B 24-I-UT-M - 1648296



HEAVYCON pin insert, B24 series, 24-pos., screw connection

Housing - HC-B 24-TFL-N-O1STM32S - 1460192



HEAVYCON B24 sleeve housing, for single locking latch, height: 65 mm, with 1 x M32 thread, lateral cable outlet

Housing - HC-B 24-AMLD - 1771943



HEAVYCON B24 panel mounting base, with single locking latch, height: 29 mm, with plastic cover, with flat gasket



Connector set - HC-KIT-B24-R02 - 1409752

Articles in set

Contact insert - HC-B 24-I-UT-F - 1648306



HEAVYCON female insert, B24 series, 24-pos., screw connection

| Approvals | | |
|------------------|-----|--------------------------|
| Approvals | | |
| | | |
| Approvals | | |
| EAC / EAC | | |
| Ex Approvals | | |
| Approval details | | |
| EAC | ERC | RU C- DE.Al30.B.01102 |
| | | |
| EAC | ERC | EAC-Zulassung |

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com