

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

Audio Chassis Mount *140 Series*



Note: This product line will soon be discontinued as a stocked series. Available while quantities last. It has been replaced with **140EX Series**. For alternative solution assistance, please contact Hammond Customer Service - sales@hammfg.com or USA (716) 630-7030, Canada and International (519) 822-2960.



Features

- Insulated leads 5" (127mm) long minimum
- Stamped steel case - Diameter of 1.25" (31.8mm) and height of 1" (25.4mm) for excellent shielding - low hum pick-up.
- Frequency response 70 Hz. - 11 Khz. (+/- 1 db, ref. @ 1 Khz.)
- Case bracket - mounting hole centers are 1.9" (48.3mm)
- Net weight 2 oz.



Part No.	Typical Applications	Nominal Impedance (Ohms)		Overall Turns Ratio Pri. to Sec.	Lead Length	Case Height	Case Diameter	Mounting Holes
		Primary	Secondary					
140A	Voice Coil to Single Grid	4	60000	1:122	5.00	1.00	1.25	1.90
140B	Dyn. MIC. to Single Grid	30	60000	1:45	5.00	1.00	1.25	1.90
140C	MIC. to Single Grid	50	60000	1:34:5	5.00	1.00	1.25	1.90
140H	Bridging Line to P.P. Grids	10000	40000 ct	1:2	5.00	1.00	1.25	1.90
140K	MIC. to Single Grid	150	60000	1:2	5.00	1.00	1.25	1.90
140M	CRYS, MIC. to Base	100K	1500	8:1	5.00	1.00	1.25	1.90
140N	Dyn. MIC to Base	50	1500	1:5:5	5.00	1.00	1.25	1.90
140P	Line to Base	150/600	600/2400	1:2	5.00	1.00	1.25	1.90
140Q	Line to Line	600 ct	600 ct	1:1	5.00	1.00	1.25	1.90

Data subject to change without notice