



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Housing - HC-HPR-B10-BFH-EMR-BK - 1411083

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



HEAVYCON B10 panel mounting base, HPR series, for screw locking, for increased environmental and EMC requirements

Why buy this product

- Vibration and shock: IEC 61373/EN 50155, category 1, class 1B



Key Commercial Data

| | |
|--------------------------------------|----------|
| Packing unit | 1 STK |
| Weight per Piece (excluding packing) | 160.0 g |
| Custom tariff number | 85389099 |
| Country of origin | China |

Technical data

Dimensions

| | |
|-------------------------------|--------|
| Height | 20 mm |
| Width | 58 mm |
| Length | 145 mm |
| Length of the assembly cutout | 48 mm |
| Width of the assembly cutout | 35 mm |

Ambient conditions

| | |
|--------------------------------------|-----------------------|
| Degree of protection of housing (IP) | IP68 (0.5 bar / 24 h) |
| | IP69K |
| Ambient temperature (operation) | -40 °C ... 125 °C |

General

Housing - HC-HPR-B10-BFH-EMR-BK - 1411083


Technical data

General

| | |
|---------------------------|--|
| Note | For contact inserts HC-B10, BB18, DD42, M, K8/24 |
| Size | B10 |
| Housing type | Panel mounting base |
| Locking type | for M6 screws |
| Torque | 4 Nm (Locking screw) |
| Screw connection | none |
| Housing material | Aluminum die-cast |
| Housing surface material | Powder-coated, black |
| Seal material | NBR |
| Material lock | Stainless steel |
| Material of locking screw | Stainless steel |


Drawings

Dimensional drawing



Dimensional drawing

Dimensional drawing



Panel cutout

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 5.1 | 27143424 |
| eCl@ss 6.0 | 27261203 |
| eCl@ss 8.0 | 27440202 |
| eCl@ss 9.0 | 27440202 |

ETIM

| | |
|----------|----------|
| ETIM 4.0 | EC000437 |
| ETIM 5.0 | EC000437 |

Housing - HC-HPR-B10-BFH-EMR-BK - 1411083

Approvals

Approvals

Approvals

EAC / GL

Ex Approvals

Approvals submitted

Approval details

| |
|-----|
| EAC |
|-----|

| |
|----|
| GL |
|----|
