



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Cable gland - G-ESSWU-M40-L66L-NTES-S - 1411097

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Nickel-plated brass, Application: Ex, External cable diameter 27.9 mm ... 40.4 mm, Shielding: No, Connecting thread: M40, Color: silver

Product Features

-
- Armor connected via PE cone



Key Commercial Data

| | |
|--------------------------------------|----------------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 680.0 g |
| Custom tariff number | 74199990 |
| Country of origin | United Kingdom |

Technical data

Dimensions

| | |
|---------------------------------|---|
| Length | 93 mm |
| Wrench size, union nut | 55 mm |
| Wrench size, support | 55 mm |
| Hexagon angular dimension GRP | 60.5 mm |
| Length of the connecting thread | 15 mm |
| External cable diameter | 27.9 mm ... 40.4 mm |
| Armor connection method | Cone |
| Armor thickness | 1.6 mm ... 2 mm (Stepped cone side (SWA/...)) |
| | 0 mm ... 1.2 mm (Grooved cone side (STA/...)) |
| Cable diameter without armor | 32.2 mm (Filler beneath the armor) |

Cable gland - G-ESSWU-M40-L66L-NTES-S - 1411097

Technical data

Ambient conditions

| | |
|---------------------------------|---|
| Degree of protection | IP66 (using the corresponding A-SEW-...P-W flat gasket) |
| | IP67 (using the corresponding A-SEW-...P-W flat gasket) |
| | IP68 (using the corresponding A-SEW-...P-W flat gasket) |
| Ambient temperature (operation) | -60 °C ... 130 °C |

General

| | |
|--------------------------------|---------------------------|
| Cable gland material | Nickel-plated brass |
| Seal material | EPDM |
| Cable seal material | EPDM |
| O-ring material | Viton |
| Thread type on connection side | M40 |
| Color | silver |
| Standards/specifications | EN 60079-0, -7, -15, -31 |
| | IEC 60079-0, -7, -15, -31 |
| | EN 50262 |
| | BS 6121: Part 1:1989 |
| | IEC 62444 |
| Manufacturer | CMP |
| Manufacturer Designation | C2K, thread size 40 |

Standards and Regulations

| | |
|-----------------------|--|
| Standards/regulations | EN 60079-0, -7, -15, -31 |
| | IEC 60079-0, -7, -15, -31 |
| | EN 50262 |
| | BS 6121: Part 1:1989 |
| ATEX | Sira 13ATEX1070X |
| | Sira 13ATEX4076X |
| | Ex II 2G, II 1D, Ex e IIC Gb, Ex ta IIIC Da, Ex II 3G Ex nR IIC Gc |
| IECEX | IECEX SIR 13.0025X |
| | Ex e IIC Gb, Ex nR IIC Gc, Ex ta IIIC Da |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 5.1 | 27149109 |
| eCl@ss 6.0 | 27149109 |
| eCl@ss 8.0 | 27149109 |

Cable gland - G-ESSWU-M40-L66L-NTES-S - 1411097

Classifications

ETIM

| | |
|----------|----------|
| ETIM 4.0 | EC000441 |
| ETIM 5.0 | EC000441 |

Drawings

Dimensional drawing

