



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Screw plug - A-EXSH-M63-68L-N-S - 1411115

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Screw plug, Nickel-plated brass, Application: Ex, Connecting thread: M63, Color: silver



Key Commercial Data

| | |
|--------------|---------------|
| Packing unit | 1 STK |
| GTIN | |
| GTIN | 4046356922302 |

Technical data

Dimensions

| | |
|----------------------------------|--------|
| Length | 24 mm |
| Length without connecting thread | 9 mm |
| Connecting thread diameter | 63 mm |
| Thread pitch | 1.5 mm |
| Wrench size, union nut | 65 mm |
| Hexagon angular dimension | 77 mm |
| Length of the connecting thread | 15 mm |

Ambient conditions

| | |
|---------------------------------|--|
| Degree of protection | IP66 (using the corresponding A-SEW-...P-W flat gasket) |
| | IP68 (using the corresponding A-SEW-...P-W flat gasket) |
| Ambient temperature (operation) | -60 °C ... 200 °C (-70°C ... 100°C, when using the A-SEW-...P-W flat gasket) |

General

| | |
|--------------------------------|---|
| Note | This item must only be used with counter nut 1411248 A-INL-M63-N-S for the Ex e type of protection. |
| Material | Nickel-plated brass |
| Thread type on connection side | M63 |

Screw plug - A-EXSH-M63-68L-N-S - 1411115

Technical data

General


| | |
|----------------------------|--|
| Color | silver |
| Assembly instructions | Sealed to IP66/IP68 thanks to the use of the A-SEW-63-P-W flat gasket (item 1411288) |
| Standards/specifications | EN 60079-0, -1, -7 |
| | IEC 60079-0, -1, -7 |
| | EN 61241-0, -1 |
| | IEC 61241-0, -1 |
| Suited for EX-applications | yes |

Standards and Regulations

| | |
|-----------------------|--|
| Standards/regulations | EN 60079-0, -1, -7 |
| | IEC 60079-0, -1, -7 |
| | EN 61241-0, -1 |
| | IEC 61241-0, -1 |
| ATEX | Sira 01ATEX1284U |
| | Sira 02ATEX1003X |
| | Ex II 2 GD Ex d IIC & Ex e II, Ex IM2 Ex d I, Ex e I |
| IECEX | IECEX SIR 07.0056X |
| | Ex d I / Ex e I / Ex d IIC / Ex e II, Ex tD A21 IP6X |

Drawings

Dimensional drawing



Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>