

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









# Cable gland - G-INS-M63-L68N-NNES-S - 1411169

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Cable gland, Cable gland material: Brass, nickel-plated, External cable diameter 34 mm ... 44 mm, Shielding: No, Connecting thread: M63, Color: silver

The illustration shows version G-INS-M25-M68N-NNES-S



## **Key Commercial Data**

Packing unit	1 pc
Custom tariff number	74199990
Country of origin	Turkey

#### Technical data

#### **Dimensions**

Length	65 mm
Wrench size, union nut	64 mm
Wrench size, support	68 mm
Hexagon angular dimension GRP	70 mm
Length of the connecting thread	14 mm
Feed-through hole diameter	63.1 mm 63.3 mm
External cable diameter	34 mm 44 mm

### Ambient conditions

Degree of protection	IP69K
	IP68 (5 bar, 30 min.)
	IP66
	4X
Ambient temperature (operation)	-20 °C 100 °C (static)

#### General

No. of conductors	1



# Cable gland - G-INS-M63-L68N-NNES-S - 1411169

## Technical data

#### General

Cable gland material	Brass, nickel-plated
Seal material	Neoprene
Cable seal material	Neoprene
O-ring material	NBR
Shielded	No
Thread type on connection side	M63
Torque	25 Nm (Union nut)
Color	silver

### Classifications

## eCl@ss

eCl@ss 5.1	27081002
eCl@ss 6.0	27081002
eCl@ss 8.0	27149109

#### **ETIM**

ETIM 4.0	EC000441
ETIM 5.0	EC000441

## Approvals

Approvals

Approvals

UL Listed / cUL Listed / cULus Listed

Ex Approvals

Approvals submitted


## Approval details





# Cable gland - G-INS-M63-L68N-NNES-S - 1411169


## Approvals





# Drawings

### Dimensional drawing



Dimensional drawing

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com