



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



FO connectors - FOC-C-SCRJ-GOF-MM/10 - 1411300

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



SC-RJ connector, with long bend protection, multi-mode 50/125 µm, beige, value pack: 10 pcs.

Product Description

SC-RJ connector, for wires 2.0 to 3.0 mm in diameter, multi-mode 50/125 µm.

The reusable connector is particularly suitable for quick and easy field connection, as there is no need for bonding and polishing.

Value pack: 10 pcs.

Why buy this product

- suitable for quick and easy field assembly or repair
- No bonding or polishing
- Reusable connectors
- A real alternative to splicing
- Optimum attenuation values with easy assembly
- Long-term durability, thanks to the latest index matching gel
- the 8° fiber transition ensures optimum return loss (RL)
- meets IEC 61754-4 (SC) and FprEN 50377-17-1 (connectors for field assembly)
- Cleave technology
- Reusable connectors

Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	80.0 g
Custom tariff number	85367000
Country of origin	Bulgaria

Technical data

Mechanical characteristics

Locking type	Clip locking
Fiber type	Quartz fiber
Fiber	50/125 µm
Ferrule diameter	2.50 mm

FO connectors - FOC-C-SCRJ-GOF-MM/10 - 1411300

Technical data

Mechanical characteristics

Insertion/withdrawal cycles	≥ 500 (according to IEC 61300-2-2)
Connection method	mechanical splice
Type of contact	Index matching gel with extended temperature range
Max. cable diameter	2 mm ... 3 mm
Cable exit	straight
Type of cable	For all common cable types
Cable structure	Semi-loose compact wires (STB)
Color	beige
Wire diameter	2 mm ... 3 mm

Ambient conditions

Ambient temperature (operation)	-10 °C ... 60 °C (IEC 61300-2)
Degree of protection	IP20

Material data

Flammability rating according to UL 94	V0
Ferrule material	Zirconia ceramics

Line characteristics

Type of cable	For all common cable types
Cable type	Fiberglass
Cable structure	Semi-loose compact wires (STB)
Number of fibers	1
Fiber type	Multi-mode fiberglass
Fiber	GOF
Attenuation	≤ 0.5 dB ((95%) according to IEC 61300-3-34)
	≤ 0.2 dB ((typical value) according to IEC 61300-3-34)
Tensile strength short-term/long-term	70N (120s.) bei Aderdurchmesser >2 mm
cable layer type	Indoors

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Classifications

eCl@ss

eCl@ss 5.1	27260701
eCl@ss 6.0	27180802
eCl@ss 8.0	19170122

FO connectors - FOC-C-SCRJ-GOF-MM/10 - 1411300

Classifications

eCl@ss

eCl@ss 9.0	19170122
------------	----------

ETIM

ETIM 5.0	EC001122
----------	----------

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details

EAC

Accessories

Accessories

Assembly tool

FO accessories - FOC-TOOL-FERRULECLEANER-2.50 - 1407029



2.50 mm ferrule cleaner, for ST, SC, FC, E2000 (also APC), approx. 500 cleaning cycles

Data cable by the meter

FO connectors - FOC-C-SCRJ-GOF-MM/10 - 1411300

Accessories

FO cable - FOC-OE-OE-GZ01/... - 1411561



Fiber optic cable, multi-mode fiberglass 50/125 µm, OM2, length: various

FO cable - FOC-OE-OE-GZ02/... - 1411563



Fiber optic cable, multi-mode fiber glass 50/125 µm, OM3, length: various

FO cable - FOC-OE-OE-GZ03/... - 1411564



Fiber optic cable, multi-mode fiberglass 50/125 µm, OM4, length: various

Tool set

Tool set - FOC-TOOL-GOF KONF SET - 1411049



Tool set for GOF assembly

Necessary add-on products

Tool set - FOC-TOOL-GOF KONF SET - 1411049



Tool set for GOF assembly

FO connectors - FOC-C-SCRJ-GOF-MM/10 - 1411300

Accessories

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>