

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







Mechanical data (according to IEC 61076-2-101)		Material			
no. of poles / coding	4 / A	housing / surface	GD-Zn / Ni		
contact termination	crimp / pin	contact carrier	PA 66 / UL 94 VO		
contact-∅	1mm colour		black		
temperature range	-40°C / +85°C	wire	TPE		
protection class	IP 67	cross section	0,34mm ²		
mating cycles	>100	contacts / surface	CuZn / Au		
locking system	M12 STANDARD	sealing gasket	FKM		
tocking system		potting	PU 2k / UL 94 V0		

further information:

- see technical data M12-1

see installation recommendation M16x1,5 design DSI XL

nut enclosed


M12×1

order-no.


L (m)


separately

10,2



All specified data refers to the mounted M12 installation plugs \geq IP54 and requires that the connector pair be correctly plugged and locked. Influences from wires, cables or PCB mounting are also to be taken into consideration.





Pin layout

pin	colour
1	brown
2	white
3	blue
4	black

					14 115 9 1	0,5
general tolerance acc. to DIN ISO 2768-c		ance	hh-:	technical changes reserved Index 1 / 2013-11-05		scale:
		2768-с				2:1
	date	name	description:			
esign	2013-11-05	Scheerer				
chk.			Rear mounting (M16x1,5)			page: 1
						of: 1



drawing-no.:	BA-L11RSCOBX,XX (X,XX=L)	docno.:	007	57023
order-no.:	see chart			
article designation:	SACC-DSI-M12MS-4P-M16XL/L (se	e chart)		