imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Patch cable - NBC-R4AC1/3,0-94G/R4AC1-BU - 1413162

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Patch cable, contact inserts: x , degree of protection: IP20, cable length: 3 m, number of positions: 8, 10 Gbps, $CAT6_A$

RoHS

Key Commercial Data

| Packing unit | 1 STK |
|--------------|-----------------|
| GTIN | 4 046356 989978 |
| GTIN | 4046356989978 |

Technical data

Dimensions

| Length of cable | 3 m |
|--------------------|-----|
| Ambient conditions | |

| Degree of protection | IP20 |
|---------------------------------|-------------------------------|
| Ambient temperature (operation) | -25 °C 60 °C (RJ45 connector) |

General data

| Rated current at 40°C | 0.5 A |
|-----------------------|-----------|
| Rated voltage | 48 V |
| Number of positions | 8 |
| Rated voltage (III/3) | 72 V (DC) |

Environmental Product Compliance

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
| | No hazardous substances above threshold values |

Drawings




Patch cable - NBC-R4AC1/3,0-94G/R4AC1-BU - 1413162

Schematic diagram

87654321

Dimensional drawing



Connector pin assignment plug RJ45

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

EHC

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com B.00767