



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# Housing - HC-ADV-B10-HHWH-1STM32-EMC-AL - 1413403

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



HEAVYCON ADVANCE sleeve housing, B10, with stainless steel screw locking (Allen screw), salt-water-resistant aluminum, height 93.7 mm, with 1x M32 thread, lateral cable outlet, without surface; conductive seal (EMC properties)



## Key Commercial Data

|              |               |
|--------------|---------------|
| Packing unit | 1 STK         |
| GTIN         |               |
| GTIN         | 4055626030371 |

## Technical data

### Dimensions

|                               |         |
|-------------------------------|---------|
| Height                        | 93.7 mm |
| Width                         | 57 mm   |
| Length                        | 105 mm  |
| Length of the assembly cutout | 65 mm   |
| Width of the assembly cutout  | 35 mm   |

### Ambient conditions

|  |                           |
|--|---------------------------|
| Degree of protection of housing (IP)   | IP66                      |
|  | IP68 (0.2 bar/24 h)       |
|  | IP69K (ISO 20653:2013-02) |
| Degree of protection of housing (NEMA) | 4 (UL 50e)                |
|  | 4X (UL 50e)               |
|  | 12 (UL 50e)               |
| Ambient temperature (operation)        | -40 °C ... 125 °C         |

### General

|      |  |
|------|--|
| Note | For contact inserts HC-B10, BB18, DD42, M, K8/24 |
|------|--|

# Housing - HC-ADV-B10-HHWH-1STM32-EMC-AL - 1413403

## Technical data

### General


|                              |   |
|------------------------------|---|
| Size                         | B10   |
| Housing type                 | Sleeve housing  |
| Locking type                 | Screw locking   |
| Torque                       | 3 Nm (Locking screw)  |
| Fixing screws                | M6 (screw head: 5 mm Allen screw)   |
| No. of cable outlets         | 1   |
| Cable exit                   | lateral   |
| Screw connection             | none  |
| Type of the screw connection | 1x M32  |
| Housing material             | Die-cast aluminum, salt water resistant   |
| Housing surface material     | Uncoated  |
| Seal material                | NBR, conductive   |
| Material lock                | Stainless steel   |
| Assembly instructions        | In order to guarantee that the ground conductor contact functions even when plugged in at an angle, the two panel mounting flanges must have sufficient electrical contact with the metal mounting panel. |
| Connection                   | To ensure optimum shielding, any insulating power coating must be removed from the profile gasket area on the control cabinet panel.<br>Tightening torque of locking screw: 3 Nm.                         |

### Environmental Product Compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

## Drawings

Dimensional drawing



Panel cutout

<sup>2)</sup> When self-tapping screws are used (Torx® 20, M4)

## Approvals

### Approvals

Approvals






EAC / GL / UL Recognized / cUL Recognized / cULus Recognized

# Housing - HC-ADV-B10-HHWH-1STM32-EMC-AL - 1413403

## Approvals

Ex Approvals

### Approval details

|                  |   |   |                     |
|------------------|---|---|---------------------|
| EAC              |    |   | 7500651.22.01.00246 |
| GL               |    | <a href="http://exchange.dnv.com/tari/">http://exchange.dnv.com/tari/</a>   | 6196614 HH          |
| UL Recognized    |   | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E255026             |
| cUL Recognized   |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E255026             |
| cULus Recognized |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> |                     |

Phoenix Contact 2017 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>