



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Cable gland - G-INB-M20-S68N-PEPDS-LG - 1415174

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Polyamide, Application: Standard, External cable diameter 6 mm ... 13 mm, Shielding: No, Connecting thread: M20

The figure shows version G-INB-M25-M68N-PEPDS-LG



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	22.0 g
Custom tariff number	39269097
Country of origin	Germany

Technical data

Dimensions

Length	103 mm
Length without connecting thread	91 mm
Connecting thread diameter	20 mm
Wrench size, union nut	24 mm
Wrench size, support	24 mm
Hexagon angular dimension GRP	27 mm
Length of the connecting thread	12 mm
External cable diameter	6 mm ... 13 mm

Ambient conditions

Degree of protection	IP68 (5 bar / 0.5 h)
	IP69K
Ambient temperature (operation)	-40 °C ... 100 °C (static)

General

Cable gland - G-INB-M20-S68N-PEPDS-LG - 1415174

Technical data

General

Cable gland material	Polyamide
Seal material	EPDM
Shielded	No
Thread type on connection side	M20
Color	light grey RAL 7035

Classifications

eCl@ss

eCl@ss 5.1	27149109
eCl@ss 6.0	27149109

ETIM

ETIM 5.0	EC000441
----------	----------

Approvals

Approvals


Approvals

UL Recognized / cUL Recognized / GOST-R / cULus Recognized

Ex Approvals

Approvals submitted


Approval details



Cable gland - G-INB-M20-S68N-PEPDS-LG - 1415174

Approvals

GOST-R 

cULus Recognized 

Drawings

Dimensional drawing

