



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us



Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



PART NUMBER	ITEM ① BODY	ITEM ② CONTACT	ITEM ③ INSULATOR
142-D7D1-B01	BRASS GOLD PL .00001 MIN OVER NICKEL PL .00005 MIN OVER COPPER PL .00005 MIN	BERYLLIUM COPPER GOLD PL .00005 MIN OVER NICKEL PL .00005 MIN OVER COPPER PL .00005 MIN	TEFLON
142-D7D1-B06	BRASS NICKEL PL .0001 MIN OVER COPPER PL .00005 MIN	BERYLLIUM COPPER GOLD PL .00005 MIN OVER NICKEL PL .00005 MIN OVER COPPER PL .00005 MIN	TEFLON



NOTES:

1. SPECIFICATIONS:

IMPEDANCE: 50 OHMS
 FREQUENCY RANGE: D-18 GHz
 VSWR: NOT APPLICABLE
 WORKING VOLTAGE: 335 VRMS MAX AT SEA LEVEL
 DIELECTRIC WITHSTANDING VOLTAGE: 1000 VRMS MIN AT SEA LEVEL
 INSULATION RESISTANCE: 5000 MEGOHM MIN
 CONTACT RESISTANCE:
 CENTER CONTACT - INITIAL 3.0 MILLIOHM MAX, AFTER ENVIRONMENTAL 4.0 MILLIOHM MAX
 OUTER CONDUCTOR - INITIAL 2.0 MILLIOHM MAX AFTER ENVIRONMENTAL NOT APPLICABLE
 BRAID TO BODY - NOT APPLICABLE
 CORONA LEVEL: 250 VOLTS MIN AT 70,000 FEET
 INSERTION LOSS: NOT APPLICABLE
 RF LEAKAGE: NOT APPLICABLE
 RF HIGH POTENTIAL WITHSTANDING VOLTAGE: 670 VRMS MIN AT 4 AND 7MHz

MECHANICAL:

ENGAGE/DISENGAGE TORQUE: 2 INCH-POUNDS MAX
 MATING TORQUE: 7-10 INCH POUNDS
 COUPLING PROOF TORQUE: NOT APPLICABLE
 COUPLING NUT RETENTION: NOT APPLICABLE
 CONTACT RETENTION: 6 LBS MIN AXIAL FORCE
 4 IN-OZ MIN RADIAL TORQUE
 CABLE ACCEPTABILITY: NOT APPLICABLE
 CABLE HEX CRIMP SIZE: NOT APPLICABLE
 CABLE RETENTION: NOT APPLICABLE
 DURABILITY: 500 CYCLES MIN

ENVIRONMENTAL:

(MEETS OR EXCEEDS THE APPLICABLE PARAGRAPH OF MIL-PRF-39012)
 THERMAL SHOCK: MIL-STD-202, METHOD 107, CONDITION B
 OPERATING TEMPERATURE: -65 DEG C TO 165 DEG C
 CORROSION: MIL-STD-202, METHOD 101, CONDITION B
 SHOCK: MIL-STD-202, METHOD 213, CONDITION I
 VIBRATION: MIL-STD-202, METHOD 204, CONDITION D
 MOISTURE RESISTANCE: MIL-STD-202, METHOD 106

DRAWING NO. C - 142-0701-801/810	
0 REVISIONS	
ENGINEERING RELEASE	
03	01-12-89 [E] [J] [H] [S] [M] [L] [K] [J] [I] [H] [G] [F] [E] [D] [C] [B] [A] 6-14-89 ECO 23856
ADDED: 2X .075±.005, .065±.010, .187±.010 DELETED: .573±.015, .562±.010 CHANGED: UPDATED GRAPHICS, .040±.005 WAS ±.010.	
4	7-16-90 [H] [S] [M] [L] [K] [J] [I] [H] [G] [F] [E] [D] [C] [B] [A]
VERSION UPDATE	
5	9-6-91 [R] [H] [S] [M] [L] [K] [J] [I] [H] [G] [F] [E] [D] [C] [B] [A] 9-17-91 ECO 40532
ADDED: NOTE 2, .025±.010 CHANGED: 2X .068±.003 WAS 2X .068±.003	
6	10-21-92 [R] [H] [S] [M] [L] [K] [J] [I] [H] [G] [F] [E] [D] [C] [B] [A] 12-18-92 ECO 41345
CHANGED: .068±.007 WAS .068±.006, UPDATED GRAPHICS	
6a	2-21-94 [R] [H] [S] [M] [L] [K] [J] [I] [H] [G] [F] [E] [D] [C] [B] [A] 3-8-94 ECO 42220
CHANGED: -.805 "R", .075/.055 WAS .068±.007 AND "C", .071/.055 WAS .068±.003	
6b	6-13-94 [R] [H] [S] [M] [L] [K] [J] [I] [H] [G] [F] [E] [D] [C] [B] [A] 6-21-94 ECN 42516
ADDED: .000 MAX PROJECTION, CUT AWAY FLANGE DETAIL CHANGED: 2X .068±.003 WAS 2X "C", .068±.007 WAS "B", 4X .040±.004 WAS 2X .040±.004 DELETED: .025±.005, NOTE 7 TABULATED DIMENSIONS "B", "F" & "C" & REMARKS, P/N 142-0701-B05	
7	10-24-96 [R] [H] [S] [M] [L] [K] [J] [I] [H] [G] [F] [E] [D] [C] [B] [A] ECN 44272
VERSION UPDATE	
B	2-26-99 [R] [H] [S] [M] [L] [K] [J] [I] [H] [G] [F] [E] [D] [C] [B] [A] ECN 46211
VERSION UPDATE	
* REVISION NUMBER FOLLOWED BY AN ALPHA * * CHARACTER INDICATES DRAWING CLASS - * * CATION OR PART NUMBER ADDITION ONLY. *	
8a	8-13-01 [R] [H] [S] [M] [L] [K] [J] [I] [H] [G] [F] [E] [D] [C] [B] [A] ECN 47953

CUSTOMER DRAWING

THIS DRAWING TO BE INTERPRETED PER ANSI Y 14.5M - 1982

"μSTATION"

COMPANY CONFIDENTIAL

TOLERANCE UNLESS OTHERWISE SPECIFIED	DRAWN BY EJ	DATE 1-12-89	JOHNSON Cinch Connectivity Solutions 299 Johnson Ave. Ste. 100 Muskegon, MI 49525 1-800-247-8256	
DECIMALS .XX	CHECKED BY RJE	DATE 6-12-89	TITLE JACK ASSEMBLY END LAUNCH SMA	
.XXX	APPROVED BY	DATE	CODE NO.	DRAWING NO.
MATL	APPROVED BY	DATE	C - 142-0701-801/810	
FINISH	RELEASE DATE	6-14-89	SCALE 10:1	U/M INCH SHEET 2 OF 2