

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







	ITEM 1	ITEM 2	ITEM 3	ITEM (4)	ITEM 5	ITEM 6
PART NUMBER	BODY	CONTACT	INSULATOR	CRIMP SLEEVE	LOCKWASHER	NUT
142-9303-411	COPPER ALLOY GOLD PL .00005 MIN OVER COPPER PL .00005 MIN	BERYLLIUM COPPER GOLD PL .00005 MIN OVER COPPER PL .00005 MIN	TEFLON	COPPER ALLOY GOLD PL .00005 MIN OVER COPPER PL .00005 MIN	COPPER ALLOY GOLD PL .00005 MIN OVER COPPER PL .00005 MIN	COPPER ALLOY GOLD PL .00005 MIN OVER COPPER PL .00005 MIN
142-9303-414	COPPER ALLOY SILVER PL .00005 MIN OVER COPPER PL .00005 MIN	BERYLLIUM COPPER SILVER PL .00005 MIN OVER COPPER PL .00005 MIN	TEFLON	COPPER ALLOY SILVER PL .00005 MIN OVER COPPER PL .00005 MIN	COPPER ALLOY SILVER PL .00005 MIN OVER COPPER PL .00005 MIN	COPPER ALLOY SILVER PL .00005 MIN OVER COPPER PL .00005 MIN



NOTES:

1. SPECIFICATIONS:

IMPEDANCE: 50 OHMS FREQUENCY RANGE: 0-12.4 GHz VSWR: 1.15+.02 F MAX (F IN GHz) WORKING VOLTAGE: 250 VRMS MAX AT SEA LEVEL DIELECTRIC WITHSTANDING VOLTAGE: 750 VRMS MIN AT SEA LEVEL INSULATION RESISTANCE: 5000 MEGOHM MIN CONTACT RESISTANCE: CENTER CONTACT - INITIAL 3.0 MILLIOHM MAX, AFTER ENVIRONMENTAL 4.0 MILLIOHM MAX OUTER CONDUCTOR - INITIAL 2.0 MILLIOHM MAX AFTER ENVIRONMENTAL NOT APPLICABLE BODY TO CABLE - 0.5 MILLIOHM MAX (GOLD PLATED) 5.0 MILLIOHM MAX (NICKEL PLATED) CORONA LEVEL: 190 VOLTS MIN AT 70,000 FEET INSERTION LOSS: .06/F dB MAX (F IN GHz) AT 6 GHz RF LEAKAGE: -60 DB MIN AT 2.5 GHz RF HIGH POTENTIAL WITHSTANDING VOLTAGE: 500 VRMS MIN AT 4 AND 7 MHz

MECHANICAL:


ENGAGE/DISENGAGE TORQUE: 2 INCH POUNDS MAX MATING TORQUE: 7-10 INCH POUNDS COUPLING PROOF TORQUE: NOT APPLICABLE COUPLING NUT RETENTION: NOT APPLICABLE CONTACT RETENTION: 6 LBS MIN CABLE ACCEPTABILITY: RG 188, RG 316 RG 161, RG 174 CABLE HEX CRIMP SIZE: .128 CONTACT CRIMP TOOL: MIL M22520/1-01 CABLE RETENTION: 20 LBS MIN AXIAL FORCE DURABILITY: 500 CYCLES MIN


ENVIRONMENTAL:

(MEETS OR EXCEEDS THE APPLICABLE PARAGRAPH OF MIL-PRF-39012) THERMAL SHOCK: MIL-STD-202, METHOD 107, CONDITION B, EXCEPT 85° C HIGH TEMP

OPERATING TEMPERATURE: -65° C TO 165° C

CORROSION: MIL-STD-202, METHOD 101, CONDITION B SHOCK: MIL-STD-202, METHOD 213, CONDITION I VIBRATION: MIL-STD-202, METHOD 204, CONDITION D MOISTURE RESISTANCE: MIL-STD-202, METHOD 106





4:1

DATE DRAWN BY TOLERANCE UNLESS OTHERWISE SPECIFIED RJB 5-14-07 DECIMALS CHECKED BY DATE .XX RJB 5-15-07 TITLE XXX. APPROVED BY DATE MATL 5-15-07 JCN

RELEASE DATE

SCALE

10:1

U/M INCH

FINISH

Cinch Connectivity Solutions P.O. Box 1732 Waseca, MN 56093 1-800-247-8256

DRAWING NO.

<u>) – 142-9303-411/420</u>

REVISIONS

1 5-14-07 A J J J C 5-15-07 T B U S N ECN 51027

ENGINEERING RELEASE

JACK ASSEMBLY, STRAIGHT CABLED BULKHEAD,

SMA, RG 316, NON-MAGNET

CUSTOMER DRAWING

THIS DRAWING TO BE INTERPRETED

PER ASME Y 14.5M - 1994

"LSTATION"

COMPANY CONFIDENTIAL

DRAWING NO. 1 - 142 - 9303 - 411/4202 OF 2

5-15-07 SHEET