

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China








Mechanical data (according to IEC 61076-2-101)		Material				
no. of poles / coding	3+PE / S	housing / surface	GD-Zn / Ni			
contact termination	crimp / socket	contact carrier	PA / UL 94 VO black			
contact-Ø	1,5mm	colour				
temperature range	-40°C / +85°C	cable	PUR			
protection class	IP 66 / IP 67	cross section	1,5mm ²			
mating cycles	> 100	contacts / surface	CuZn / Au			
Locking system	M12 Standard /	sealing gasket	FKM			
locking system	SPEEDCON	overmold / cable	TPU / black			


futher information:
- see technical data M12-4



The specified electrical and mechanical data require a correctly locked pair of connectors. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap >IP54.

Influences from wires, cabels or PCB mounting are also to be taken into consideration.

View of pin assignment Plug-in side



Pin layout

pin	colour				
1	black "1"				
2	black "2"				
3	black "3"				
PE	green/yellow				

order-no.	L (m)	cable-printing
1424096	1,5	ArtNr. 1424096 1,5m PUR 4x1,5 KW/JJ
1424097	3,0	ArtNr. 1424097 3,0m PUR 4x1,5 KW/JJ
1424098	5,0	ArtNr. 1424098 5,0m PUR 4x1,5 KW/JJ
1424099	10,0	ArtNr. 1424099 10,0m PUR 4x1,5 KW/JJ
1421972	15,0	ArtNr. 1421972 15.0m PUR 4x1.5 KW/JJ
1419219	25,0	ArtNr. 1424099 10,0m PUR 4x1,5 KW/JJ
1421684	30,0	ArtNr. 1421684 30,0m PUR 4x1,5 KW/JJ

general tolerance acc. to DIN ISO 2768-c		ance	technical changes reserved		Index 8 / 2015-11-06		scale:		
		2768-с					1:1		
	date	name	description:						
design	2011-09-09		. M12 Power						
chk.			socket overmolded, straight, AC					nane: 1	
			SOLKET OVERMOLUEU, STRATYM, AL page: 1 of: 1						
			drawing-no.:	KBP-4SBE01AX,	XX (X,>	(X=L)	docno.:	006	34427
	BBUÆI		1						



drawing-no.: KBP-4SBE01AX,XX (X,XX=L) doc.-no.: 00634427 order-no.: see chart
article designation: SAC-4P-FSS/L (see chart) -PUR PE SH SCO