

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Screw plug - A-INSP-M40-68N-P-LG - 1424522

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Screw plug, cable gland material: PA, PA, connecting thread: M40 x 1.5, color: lightgrey RAL 7035



Key Commercial Data

| Packing unit | 5 STK |
|------------------------|-----------------|
| Minimum order quantity | 5 STK |
| GTIN | 4 055626 374277 |
| GTIN | 4055626374277 |

Technical data

Dimensions

| Length | 13 mm |
|---------------------------------|------------------|
| Connecting thread diameter | 40 mm |
| Hexagon angular dimension | 46 mm (Diameter) |
| Length of the connecting thread | 8 mm |

Ambient conditions

| Degree of protection | IP68 |
|---------------------------------|---------------|
| | IP66 |
| Ambient temperature (operation) | -40 °C 100 °C |

General

| Material | PA |
|-----------------------------|--------------------|
| Cable gland material | PA |
| Thread type connection side | M40 x 1.5 |
| Torque | 3 Nm |
| Color | lightgrey RAL 7035 |

Standards and Regulations



Screw plug - A-INSP-M40-68N-P-LG - 1424522

Technical data

Standards and Regulations


| Halogen-free | yes |
|--------------|-----|
| | |

Environmental Product Compliance

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
| | No hazardous substances above threshold values |

Drawings

Dimensional drawing



Dimensional drawing

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC EAC-Zulassung



Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300

Fax +49 5235 3 41200

http://www.phoenixcontact.com