



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Specification Sheet

Part Number: 151-00180



Connector Clip; Hole Dia. 6.2X12.2mm; Panel 0.6-6.0mm/ PA66HIRHS; Black; 1000/Pack

Article Number	151-00180
Type	YCCFT62x122
Color	Black (BK)
Features & Benefits	•Head design contains clamping rails to provide full circumferential compression around bundles. •Bent tail allows for quick insertion into head.
Quantity Per	pcs.
Product Description	Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.
Short Description	Connector Clip; Hole Dia. 6.2X12.2mm; Panel 0.6-6.0mm/ PA66HIRHS; Black; 1000/Pack

Global Part Name

YCCFT62x122-PA66HIRHS-BK

Length L (Imperial)

0.83

Length L (Metric)

21.08

Fixation Method

Fir Tree for oval holes

Width W (Imperial)

0.63

Width W (Metric)

16.0

Height H (Imperial)

0.71

Height H (Metric)

18.0

Panel Thickness Min(Imperial)

0.02

Panel Thickness Max(Imperial)

0.24

Panel Thickness Min (Metric)

0.6

Panel Thickness Max (Metric)

6.0

Mounting Hole Diameter D (Imperial)

0.24 x 0.48

Mounting Hole Diameter D (Metric)

6.2 x 12.2 mm

Mounting Hole Diameter D Min (Imperial)

0.244

Mounting Hole Diameter D Max (Imperial)

0.48

Mounting Hole Diameter D Max (Metric)

12.2

Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909987
Content Unit(BMEcat)	pcs.
Weight (Metric)	1.18