



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Specification Sheet

Part Number: 151-02098



High Torque Mount, Mounting Hole Dia. 0.327", Max Torque 114.0 lb - ft, PA66HIRHSUV, Black, 100/pkg

Article Number	151-02098
Type	HDM320
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Mount and tie combination makes it easy to service bundles in the field.• Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments.• Eliminates the needs for multiple sized fix diameter clamps.
Quantity Per	carton

Product Description

The high-torque mount is designed for use with power-assisted impact wrenches and is molded with a heavy bushing to withstand the forces required to tighten grade 8 bolts. The arched H-profile of the saddle surface allows for a broad surface contact with the bundle, minimizing pinching and crushing of the bundles, and adjusts to a wide variety of bundle diameters when used with HellermannTyton heavy duty T120, T250, T255 and Wide Strap Cable Ties.

Short Description

High Torque Mount, Mounting Hole Dia. 0.327", Max Torque 114.0 lb - ft, PA66HIRHSUV, Black, 100/pkg

Global Part Name

HDM320-PA66HIRHSUV-BK

Length L (Imperial)

1.85

Length L (Metric)

47.0

Fixation Method

Screw Mounting and Rivet

Width W (Imperial)

1.0

Width W (Metric)

25.0

Height H (Imperial)

0.81

Height H (Metric)

20.7

Cable Tie Width Max (Imperial)

0.5

Cable Tie Width Max (Metric)

12.7

Mounting Hole Diameter D (Imperial)

0.327

Mounting Hole Diameter D (Metric)

8.31 mm

Mounting Hole Diameter D Min (Imperial)

0.327

Mounting Hole Diameter D Max (Imperial)

0.327

Mounting Hole Diameter D Max (Metric)

8.31

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
Maximum Torque (kgf-cm)	1576.0
Maximum Torque (lbf-ft)	114.0
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	100
Package Quantity (Metric)	100
Content Unit(BMEcat)	pcs.
Weight (Metric)	0.0202
Weight (Imperial)	0.0446

