

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









# A-series AEP 2C 2.5

#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com







### **Spring connection with PUSH IN Technology**

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

### General ordering data

Туре	AEP 2C 2.5	
Order No.	<u>1514400000</u>	
Version	A-series, End plate	
GTIN (EAN)	4050118436112	
Qty.	50 pc(s).	



# A-series AEP 2C 2.5

Weidmüller Interface GmbH & Co. KG

27-14-11-33

Klingenbergstraße 16 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

# Technical data

**Dimensions and weights** 

/idth (inches) eight (inches) epth (inches) ontinuous operating temp., max.	0.083 inch 2.077 inch 1.146 inch
epth (inches)	1.146 inch
ontinuous operating temp., max.	130 °C
ontinuous operating temp., max.	130 °C
ontinuous operating temp., max.	130 °C
olour	Dark Beige
	Yes
	<i>N</i> ith snap-in pegs

Approvals
-----------

**ETIM 6.0** 

eClass 9.1

Downloads			
ROHS	Conform		

eClass 6.2

Brochure/Catalogue	CAT 1 TERM 16/17 EN
Engineering Data	EPLAN, WSCAD, Zuken E3.S

EC000886

27-14-11-33