



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




SACB- 8X0,34/2X0,75-50 PUR

Order No.: 1517592

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1517592>

Master cable for sensor/actuator boxes, without PE conductor,
unshielded, material PUR/PVC, 10-pos., 8 x 0.34 mm² and 2 x 0.75
mm², length: 50 m

Commercial data	
GTIN (EAN)	 4 017918 933319
Note	Made-to-order
sales group	D192
Pack	1 pcs.
Customs tariff	85366990
Catalog page information	Page 135 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
06/21/2006



[http://
www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)
Please note that the data given
here has been taken from the
online catalog. For comprehensive
information and data, please refer
to the user documentation. The
General Terms and Conditions of
Use apply to Internet downloads.

Technical data	
General data	
Rated voltage	300 V
Master cable data	
Length of cable	50 m

Cable type	Master cable suitable for flexible cable conduit
Signal line cross section	8x 0.34 mm ²
AWG signal line	22
Conductor structure signal line	42 0.10 mm
Power supply cross section	2x 0.75 mm ²
AWG power supply	19
Conductor structure, voltage supply	96x 0.10 mm
External diameter	8.7 mm
Max. bending cycles	1500000
Bending radius	90 mm
Traversing path	2 m
Traversing rate	2 m/s
Ambient temperature (operation)	-40 °C ... 80 °C (for fixed installation)
	-5 °C ... 80 °C (for flexible installation)

Accessories

Item	Designation	Description
Tools		
1212156	WIREFOX 4	Stripping tool, for lines and conductors (special for rubber and silicon insulations) of 0.1 - 4 mm ² , self-adjusting, stripping length up to 18 mm, cutting capacity up to 10 mm ² stranded / 1.5 mm ² solid
1212162	WIREFOX-D 13	Stripping tool, for stripping installation lines of Ø 8 - 13 mm , e.g. NYM 3 x 1.5 mm ² to 5 x 2.5 mm ² , single line stripping 0.2 mm ² - 4 mm ² , with longitudinal cut blade and sliding knife
1212161	WIREFOX-D 40	Stripping tool, for stripping lines of Ø 4.5 - 40 mm, insulation strength up to 4.5 mm

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;