imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)

Sensor/actuator box, Connection method: M5 socket Metal, Number of slots: 8, Number of positions: 3, Slot assignment: Single, Status indication: Yes, pnp; Master cable connection: M12 plug connection 90°, Shielding: No

Product Features

- ${\ensuremath{\,^{\scriptsize \Box}}}$ Safety in the field, thanks to molded housing and high degree of protection
- Flexible, distributed bundling of signals in one master cable
- Convenient: increased machine availability thanks to quick and easy diagnostics



Key commercial data

Packing unit	1 PCE
Weight per Piece (excluding packing)	61.4 GRM
Custom tariff number	85366990
Country of origin	Germany

Technical data

General

Rated voltage	24 V DC
Max. operating voltage U _{max}	30 V DC
Current carrying capacity per I/O signal	1A
Current carrying capacity per slot	1 A
Total rated current	3 A
Number of positions	3
Number of slots	8
Inflammability class according to UL 94	V0
Sensor/actuator connection system	M5 socket
Ambient conditions	
Degree of protection	IP67



Technical data

Ambient conditions

Ambient temperature (operation)	-25 °C 80 °C
Local diagnostics function	
Local diagnostics	Supply voltage Green LED
	Status display I/O Yellow LED
Master cable data/connection data	
Connection method	M12 plug connection
Insulation material	
Housing material	PA-GF
Contact material	CuZn
Contact surface material	Ni/Au
Material of threaded sleeve	Cu alloy
Material of threaded sleeve surface	Nickel-plated
Pin assignment	
Slot/position = Wire color or connection	1 / 4 (A) = 3
	2 / 4 (A) = 4

3 / 4 (A) = 6
4 / 4 (A) = 8
5 / 4 (A) = 5
6 / 4 (A) = 9
7 / 4 (A) = 7
8 / 4 (A) = 10

Classifications

eCl@ss

eCl@ss 4.0	27140815
eCl@ss 4.1	27140815
eCl@ss 5.0	27143423
eCl@ss 5.1	27143423
eCl@ss 6.0	27143423
eCl@ss 7.0	27449001
eCl@ss 8.0	27449001

ETIM

ETIM 2.0	EC000200
ETIM 3.0	EC001856



Classifications

ETIM

ETIM 4.0	EC002585
ETIM 5.0	EC002585

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approvals

Approvals

GOST

Ex Approvals

Approvals submitted

Approval details

GOST 🞯

Accessories

Accessories

Master cable, assembled



Accessories

Master cable - SAC-12P- 5,0-PUR/M12FS MC - 1530786



Master cable, 12-position, PUR/PVC, Black RAL 9005, Free cable end, on Socket straight M12, A-coded, Cable length: 5 m

Master cable - SAC-12P-10,0-PUR/M12FS MC - 1530799



Master cable, 12-position, PUR/PVC, Black RAL 9005, Free cable end, on Socket straight M12, A-coded, Cable length: 10 m

Protective cap

Screw plug - PROT-M5 - 1533288



An M5 screw plug for the unoccupied M5 sockets of the sensor/actuator cable, boxes and flush-type connectors

Drawings

Schematic diagram




M12 plug connection pin, 12-pos.


Schematic diagram

M5 slot, socket, 3-pos.









© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com