



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Quality Products. Service Excellence.

Sub- Miniature R.F. Chokes 1530 Series

Features



- Subminiature design ranging from only .25" to .63"
- Coils are varnish impregnated.
- Ideally suited to network, filter, delay lines etc., applications.
- L and Q values measured on a Q meter.



Part No.	Inductance L uH	Induct. Tolerance	Q Min.	Test Freq. Mhz.	Fo Min. Mhz	R - D.C. Max. Ohms	I - D.C. Max. ma.	Coil Dia. Max.	Form Length +/- .03"	Core Material
1530B106	1	+/- 20%	41	25	118	0.048	2041	0.165	0.25	Iron
1530B126	1.2	+/- 10%	45	7.9	118	0.072	1666	0.16	0.25	Iron
1530B156	1.5	+/- 10%	42	7.9	102	0.096	1443	0.16	0.25	Iron
1530B276	2.7	+/- 10%	34	7.9	74	0.168	1091	0.16	0.25	Iron
1530B336	3.3	+/- 10%	40	7.9	66	0.24	912	0.15	0.25	Iron
1530B396	3.9	+/- 10%	35	7.9	61	0.264	870	0.15	0.25	Iron
1530B476	4.7	+/- 10%	43	7.9	53	0.457	661	0.15	0.25	Iron
1530B566	5.6	+/- 10%	41	7.9	49	0.492	637	0.15	0.25	Iron
1530B686	6.8	+/- 10%	40	7.9	49	0.624	566	0.15	0.25	Iron
1530B105	10	+/- 10%	36	7.9	19	1.56	277	0.16	0.25	Iron
1530B155	15	+/- 10%	52	2.5	16	1.92	250	0.165	0.25	Iron
1530B225	22	+/- 5%	51	2.5	13	2.28	229	0.165	0.25	Iron
1530B335	33	+/- 5%	50	2.5	10	2.76	208	0.17	0.25	Iron
1530B395	39	+/- 5%	48	2.5	9.3	3.36	188	0.175	0.25	Iron
1530B475	47	+/- 5%	44	2.5	9.1	3.36	188	0.175	0.25	Iron
1530B565	56	+/- 5%	45	2.5	8.6	3.84	176	0.18	0.25	Iron
1530B685	68	+/- 5%	42	2.5	8.1	4.2	169	0.18	0.25	Iron
1530B825	82	+/- 5%	41	2.5	6.7	4.8	158	0.185	0.25	Iron
1530B104	100	+/- 5%	25	2.5	3.6	7.68	139	0.165	0.25	Iron
1530B154	150	+/- 5%	47	0.79	3	8.16	135	0.165	0.25	Iron
1530B224	220	+/- 5%	46	0.79	2.5	11.5	114	0.17	0.25	Iron
1530B334	330	+/- 5%	41	0.79	2	13.9	103	0.175	0.25	Iron
1530B474	470	+/- 5%	35	0.79	1.8	16.3	95	0.185	0.25	Iron
1530B684	680	+/- 5%	37	0.79	1.6	19.8	87	0.2	0.25	Iron
1530B824	820	+/- 5%	33	0.79	1.6	22.9	80	0.21	0.25	Iron
1530B103	1000	+/- 5%	30	0.79	1.4	24	79	0.225	0.25	Iron
1530B153	1500	+/- 5%	40	0.25	1.1	37.2	63	0.225	0.25	Iron
1530B223	2200	+/- 5%	40	0.25	0.96	45.6	57	0.24	0.25	Iron
1530C253	2500	+/- 5%	48	0.25	0.96	45.6	57	0.26	0.38	Iron
1530C333	3300	+/- 5%	52	0.25	0.8	51.6	53	0.26	0.38	Iron
1530C473	4700	+/- 5%	49	0.25	0.68	64.8	48	0.285	0.38	Iron

Part No.	Inductance L uH	Induct. Tolerance	Q Min.	Test Freq. Mhz.	Fo Min. Mhz	R - D.C. Max. Ohms	I - D.C. Max. ma.	Coil Dia. Max.	Form Length +/- .03"	Core Material
1530C683	6800	+/- 5%	51	0.25	0.64	78	43	0.31	0.38	Iron
1530C823	8200	+/- 5%	48	0.25	0.6	92.4	40	0.33	0.38	Iron
1530C102	10000	+/- 5%	41	0.25	0.52	101	38	0.335	0.38	Iron
1530C182	18000	+/- 5%	49	0.079	0.29	128	44	0.325	0.50	Iron
1530D252	25000	+/- 5%	59	0.079	0.25	115	46	0.34	0.63	Ferrite
1530D332	33000	+/- 5%	61	0.079	0.232	134	43	0.353	0.63	Ferrite
1530D101	100000	+/- 5%	48	0.079	0.157	278	29	0.446	0.63	Ferrite

Data subject to change without notice

© 2017. Hammond Manufacturing Ltd. All rights reserved.