



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832




Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China






7.62 mm Terminal Blocks




TOP 1.5 GS/7.62/90
 Single-Level
 90° Orientation
 Without Test Points
 Ex'e' Increased Safety



TOP 1.5 GS/7.62/90 BL
 Single-Level
 90° Orientation
 Without Test Points
 Ex'e' Increased Safety



TOP 1.5 GS/7.62/180
 Single-Level
 180° Orientation
 Without Test Points
 Ex'e' Increased Safety



| Technical Data | | | UL | | | BVS | | |
|---------------------|-------------------------|----------|---------------------|-------------------------|---------------------|-------|--------------------------|----------|
| Rated Voltage | BVS 250 V | | UL 90 V | | BVS 250 V | | | |
| Rated Current | 16 A | | - | | 16 A | | | |
| Wire Size | 1.5 mm ² | | 1.5 mm ² | | 1.5 mm ² | | | |
| Strip Length | 10 mm | | 10 mm | | 10 mm | | | |
| Torque Nm (lb. in.) | 0.5 (4.4) | | 0.5 (4.4) | | 0.5 (4.4) | | | |
| Pin Length | 3.5 mm | | 3.5 mm | | 3.5 mm | | | |
| Certificate No. | BVS 89 B 7001 U | | - | | BVS 89 B 7001 U | | | |
| Poles | Type | Part No. | Poles | Type | Part No. | Poles | Type | Part No. |
| 1** | TOP 1.5 GS/7.62/90/1 OG | 153976 | 1*** | TOP 1.5 GS/7.62/90/1 BL | 153978 | 1** | TOP 1.5 GS/7.62/180/1 OG | 153616 |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |

Notes: Other solder pin lengths are available upon request.
 See pages 138-141 for marking materials and other accessories.
 **End plate (AP) part no. 56978 is required.
 ***End plate (AP) part no. 56976 is required.

PCB TERMINAL BLOCKS