Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!

Contact us

![molex logo](molex® one company › a world of innovation)

Part Number: 1552209019

Status: Active

Overview: Flamar Standard and Custom Cables for Industrial Automation

Description: Flamar Distribution Box Cable, WSOR Jacket, Unshielded, 19 Circuits, 3x(0.75mm²) with Green-Yellow Ground + 16x(0.34mm²) / 3x(19 AWG) with Green-Yellow Ground + 16x(22 AWG), 10.20mm (.402") Diameter, 100.0m (328.08') Length, Black

Series image - Reference only

Documents:
Product Specification 1552209001-P1E (PDF)   Product Literature (PDF)
RoHS Certificate of Compliance (PDF)

Agency Certification
UL	E172949

General
Product Family	Cable
Series	155220
Crimp Quality Equipment	Yes
Geographic Area	Global
Overview	Flamar Standard and Custom Cables for Industrial Automation
Product Literature Order No	987651-3992
Product Name	Flamar, Signal and Control
UPC	889056463478

Physical
Bending Radius - Minimum	> 10xOD
Cable Length	100.0m
Circuits (Loaded)	19 (3+16)
Color - Cable Jacket	Black
Insulation	TPE
Material - Outer Jacket	WSOR
Net Weight	0.151/kg
Outer Jacket Diameter	10.20mm
Packaging Type	Reel
Temperature Range - Operating	-25° to +80°C
Wire Size AWG	19, 22
Wire Size mm²	0.34, 0.75
Wire/Cable Type	UL AWM 21215 / CSA

Electrical
Current - Maximum per Contact	Contact Molex
Voltage - Maximum	600V

Material Info
Engineering Number	B80-19-1X100M

Reference - Drawing Numbers
Product Specification	1552209001-P1E

EU ELV
Not Reviewed

EU RoHS   **China RoHS**
Not Reviewed

REACH SVHC
Not Reviewed

Halogen-Free Status
Not Reviewed

Need more information on product environmental compliance?

Email productcompliance@molex.com
Please visit the Contact Us section for any non-product compliance questions.

China ROHS	Not Reviewed
ELV	Not Reviewed
RoHS Phthalates	Not Reviewed

Search Parts in this Series
155220 Series

Use With
Brad M23 120230 , 120233