



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Specification Sheet

Part Number: 156-00068



Heavy-Duty Fir Tree Mount Cable Tie, 9" x .5", .04"–.26" Panel Thickness, PA66HIRHSUV, Black, 100/pkg

<b>Article Number</b>	156-00068
<b>Type</b>	WSSFT9A
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• The "H" profile provides a broad surface contact to minimize the pinching of bundles.</li><li>• Heavy duty fir tree mounts are equipped with a friction tab that will hold the tie in the mount, allowing them to be preassembled prior to installation.</li><li>• Designed specifically for HellermannTyton 120 - 250 lb. cable ties for heavy duty applications.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	HellermannTyton heavy duty fir tree mounts are designed with heavy duty applications in mind. These are optimized for up to 3 to 1 extraction versus insertion force to make assembly fast and easy. These mounts are sold as an assembly with a cable tie.

<b>Short Description</b>	Heavy-Duty Fir Tree Mount Cable Tie, 9" x .5", .04"-.26" Panel Thickness, PA66HIRHSUV, Black,100/pkg
<b>Global Part Name</b>	WSSFT9A-PA66HIRHSUV-BK
<b>Minimum Tensile Strength (Imperial)</b>	120.0
<b>Minimum Tensile Strength (Metric)</b>	535
<b>Length L (Imperial)</b>	9.0
<b>Length L (Metric)</b>	228.0
<b>Fixation Method</b>	Fir Tree
<b>Identification Plate Position</b>	none
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.5
<b>Width W (Metric)</b>	12.7
<b>Bundle Diameter Max (Imperial)</b>	2.3
<b>Bundle Diameter Max (Metric)</b>	57.0
<b>Height H (Imperial)</b>	.75
<b>Height H (Metric)</b>	19.10

<b>Panel Thickness Min(Imperial)</b>	0.039
<b>Panel Thickness Max(Imperial)</b>	0.256
<b>Panel Thickness Min (Metric)</b>	1.0
<b>Panel Thickness Max (Metric)</b>	6.5
<b>Mounting Hole Diameter D (Imperial)</b>	0.34 - 0.36
<b>Mounting Hole Diameter D (Metric)</b>	8.7 - 9.2 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.34
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.36
<b>Mounting Hole Diameter D Max (Metric)</b>	9.25
<b>Disc Diameter(Metric)</b>	21.6
<b>Disc Diameter (Imperial)</b>	0.9
<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Material Cable Tie</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-65°F to +212°F (-54°C to +100°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Package Quantity(Imperial)**

100

**Package Quantity (Metric)**

100

**Customs Number**

3926909987

**Content Unit(BMEcat)**

pcs.

**Weight (Metric)**

6.4