



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Article Number: 156-00135

Omega Clip Cable Tie, 6.0" Long, Attaches to Diameter .59" - .71", PA66HS, Black, 500/pkg



Base Data

Local Order Number	156-00135
Type	T50SVCOC15-18
Color	Black (BK)
Features and Benefits	• Omega Clip can be turned 360 degrees allowing for orientation in any direction. • Design allows quick and easy installation by hand without the need for tools. • Multiple bundle diameters available for all different ranges of bundles.
Product Description	Omega Clip Cable Ties provide the opportunity to attach a wire or hose to an existing bundle. Offering a full range of orientations, the wire/hose can be orientated in any direction in relations to the main harness. The Omega Clip design is ideally suited for easing the application process on the production floor by allowing for an easy one-step snap fit of the harness assembly to the wire or hose
Fixation Method (FF)	Omega Clips
Identification Plate Position	none
Tie Closure	plastic pawl
Short Description	Omega Clip Cable Tie, 6.0" Long, Attaches to Diameter .59" - .71", PA66HS, Black, 500/pkg

Product Dimensions

Minimum Tensile Strength (Imperial)	50.0 lbs
Minimum Tensile Strength (Metric)	222 N
Length L (Imperial)	6.0 "
Length L (Metric)	155 mm
Attaches to Diameter (Imperial)	0.6 "- 0.71 "
Width W (Imperial)	0.19 "
Width W (Metric)	4.7 mm
Bundle Diameter Min. (Imperial)	0.08 "
Bundle Diameter Min. (Metric)	2.0 mm
Bundle Diameter Max. (Imperial)	1.4 "
Bundle Diameter Max. (Metric)	35.0 mm
Diameter Min. (Imperial)	0.59 "
Diameter Max. (Imperial)	0.71 "
Thickness T (Imperial)	0.05 "
Attaches to Diameter (Metric)	15.0 - 18.0
Thickness T (Metric)	1.35 mm

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	500
Carton Quantity	3000 Pieces
Weight (Metric)	3.08 kg

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS) Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HIRHS PA66HS
Flammability	UL94 HB
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS compliant (Article 4 - 1)	Yes