



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SPECIFICATION CONTROL DRAWING

55FA/0514

| | | |
|--|-----------------|---------------|
| TITLE CABLE, ELECTRIC, FILTER LINE - ELECTROLOSS, OUTER SPACE, COMPONENT WIRE | Date 9-30-13 | Revision B |
|--|-----------------|---------------|

This specification sheet forms a part of the latest issue of Raychem Specification 55F.




TABLE I. CONSTRUCTION DETAILS

| PART NUMBER 1/ | WIRE SIZE (AWG) | CONDUCTOR STRANDING (number x AWG) | DIAMETER OF STRANDED CONDUCTOR (in.) | | FINISHED WIRE | | |
|-------------------|--------------------|---------------------------------------|---|---------|--|-------------------|----------------------------------|
| | | | MINIMUM | MAXIMUM | MAXIMUM RESISTANCE AT 20°C (ohms/1000 ft) | DIAMETER (in.) | MAXIMUM WEIGHT (lbs/1000 ft.) |
| | | | | | | | |
| 55FA/0514-26-* | 26 | 19 x 38 | .018 | .020 | 44.8 | .043 ± .002 | 2.3 |
| 55FA/0514-24-* | 24 | 19 x 36 | .023 | .025 | 28.4 | .045 ± .002 | 3.0 |
| 55FA/0514-22-* | 22 | 19 x 34 | .029 | .032 | 17.5 | .051 ± .003 | 4.0 |
| 55FA/0514-20-* | 20 | 19 x 32 | .037 | .040 | 10.7 | .059 ± .003 | 5.8 |

TABLE II. PERFORMANCE DETAILS

| PART NUMBER 1/ | BEND TESTING | | | |
|-------------------|--|-----------|--|-----------|
| | MANDREL DIAMETER (inch) (± 3%) | | WEIGHT (lb) (± 3%) | |
| | IMMERSION, LIFE CYCLE, AND CROSSLINKING PROOF TEST | COLD BEND | IMMERSION, LIFE CYCLE, AND CROSSLINKING PROOF TEST | COLD BEND |
| | | | | |
| 55FA/0514-26-* | .500 | 1.00 | .500 | 3.00 |
| 55FA/0514-24-* | .500 | 2.00 | .625 | 3.00 |
| 55FA/0514-22-* | .500 | 2.00 | .750 | 3.00 |
| 55FA/0514-20-* | .750 | 2.50 | 1.25 | 4.00 |

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics Corporation also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER. AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.

Raychem, TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks.

DIMENSIONS ARE IN INCHES, AND UNLESS OTHERWISE DESIGNATED ARE NOMINAL.

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.



Raychem Wire & Cable
501 Oakside Avenue
Redwood City, CA 94063-3800
Phone: 1-800-227-8816
Fax: 1-650-361-6297

WIRE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 150°C

Maximum continuous conductor temperature

VOLTAGE RATING: 600 volts (rms) at sea level

ATTENUATION (INSERTION LOSS): See Table III

BLOCKING: 200 ± 3°C for 6 hours

COLOR: Light violet preferred

CONCENTRICITY: Primary Insulation - 50% (minimum); Finished Wire - 70% (minimum)

CROSSLINKING PROOF TEST: 300 ± 3°C for 7 hours

FLAMMABILITY: 3 seconds (maximum); 3 inches (maximum); no flaming of facial tissue

HUMIDITY RESISTANCE: Insulation Resistance, 5000 megohms for 1000 ft. (minimum)

IDENTIFICATION AND COLOR STRIPING DURABILITY:

125 cycles (250 strokes) (minimum), 500 g weight

IMMERSION: Diameter increase 5% (maximum); no cracking, no dielectric breakdown

INSULATION ELONGATION AND TENSILE STRENGTH:

Primary Insulation, Filter Layer, and Primary Jacket pulled together

Elongation, 50% (minimum)

Tensile Strength, 3000 lbf/in² (minimum)

INSULATION FLAWS:

Primary Insulation only,

Spark Test, 1.5 kV (rms) at 60 Hz

4.2 kV (rms) at 3 KHz

Impulse Dielectric Test, 6.0 kV (peak)

Finished Wire,

Spark Test, 3.0 kV (rms) at 60 Hz

5.7 kV (rms) at 3 kHz

Impulse Dielectric Test, 8.0 kV (peak)

INSULATION RESISTANCE: 5000 megohms for 1000 ft. (minimum)

INSULATION THICKNESS:

Primary Insulation, .002 in. (minimum);

Filter Layer, average, .0025 in. (minimum);

Primary Jacket, .0035 in. (minimum)

LIFE CYCLE: 200 ± 3°C for 168 hours

LOW TEMPERATURE-COLD BEND: -65 ± 2°C for 4 hours

SHRINKAGE: 200 ± 3°C for 6 hours, 0.125 inches (maximum)

SMOKE: 200 ± 2°C, no visible smoke

SURFACE RESISTANCE: 500 megohms-in. (minimum), initial and final readings

THERMAL-SHOCK RESISTANCE: 150 ± 3°C, 0.060 inch (maximum)

THERMAL STABILITY: 180 ± 3°C for 1250 hours

VACUUM STABILITY:

Total Mass Loss (TML), 1.00% (maximum)

Volatile Condensable Material (VCM), 0.10% (maximum)

VOLTAGE WITHSTAND (Post Environmental): 1500 volts (rms), 60 Hz


WRAP TEST: 200 ± 3°C for 6 hours, no cracking

1/ PART NUMBER:

The "***" in the part numbers in Tables I-III shall be replaced by a color code designator, except that violet shall be light violet and designator shall be 7L.

Example: AWG 24, light violet: 55FA/0514-24-7L

AWG 24, light violet with a blue stripe: 55FA/0514-24-7L6



ATTENUATION (INSERTION LOSS)

| TABLE III. ATTENUATION (INSERTION LOSS) + | | | | | | | |
|---|-----------------------|----------|-------|-----------------------------|---------|----------|-----------------------|
| PART NUMBER 1/ | PASS BAND (dB/ft.) | | | TRANSITION BAND (dB/ft.) | | | STOP BAND (dB/ft.) |
| | 1.0 MHz | 10.0 MHz | | 100 MHz | 500 MHz | 1000 MHz | 1 to 12 GHz |
| | (max) | (min) | (max) | (min) | (min) | (min) | (min) |
| 55FA/0514-26-* | TBD | TBD | TBD | TBD | TBD | TBD | TBD |
| 55FA/0514-24-* | .02 | .06 | 0.20 | 1.3 | 12 | 30 | 30 |
| 55FA/0514-22-* | .02 | .06 | 0.20 | 1.3 | 12 | 30 | 30 |
| 55FA/0514-20-* | .02 | .06 | 0.20 | 1.3 | 12 | 30 | 30 |

1/ See footer section on page 1

+ THE PRIMARY WIRE OF THIS SPECIFICATION SHEET SHALL MEET THE ATTENUATION REQUIREMENTS SHOWN ABOVE ONLY WHEN USED AS A SINGLE COMPONENT IN A SHIELDED CABLE.