



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Eco-Stencil™ SMT Stencil Cleaner

Product# 1570

Product Description

Effectively removes all types of solder paste (e.g. water-based, RMA, no-clean, lead-free) and uncured adhesive from screens, misprinted boards and equipment. Completely safe on stencils, squeegees, and equipment surfaces. Ideal replacement for IPA cleaners, which are often prohibited because of safety and environmental restrictions on VOC's (Volatile Organic Compounds) or waste disposal.

One quart (with a trigger sprayer) and one gallon containers are ideal for surface and tool cleaning. Packaging is selected to be easily recyclable. Quart labels made of recycled paper, and cartons made of 40% recycled material.

Trigger pump on quart (1570-QT) eliminates the need for propellants, which can have a global warming impact. Eco-Stencil™ Cleaner is fully compliant with CARB (California Air Resource Board) requirements.

Also compliant with European REACH (Registration, Evaluation, Authorization & Restriction of Chemicals) and WEEE (Waste Electrical and Electronic Equipment Directive) initiatives. It does not contain RoHS (Restriction of Hazardous Substances) restricted substances, SVHC (Substances of Very High Concern) list substances, or halides.

Features / Benefits

- Quickly Clean Paste or Uncured Adhesive
- Safe for Stencils, Tools, Misprinted Boards
- Nonflammable
- Low VOC
- Non-Ozone Depleting
- Halide-Free – Prevents Ionic Contamination

Applications

- Manual stencil tool, work surface, and squeegee cleaning
- Automatic underside wipe stencil cleaning
- Removes unsoldered eutectic (leaded) & lead-free solder pastes
- Cleans off uncured adhesives (may require soaking)

About TECHSPRAY RENEW™

TECHSPRAY RENEW™ is a brand that represents **High Performance Eco-Cleaning™**. Techspray® has applied our expertise in solvent cleaning to formulate some of the most effective eco-friendly cleaners on the market. Performance is our top priority, using the best “green” solutions as they become available. We all are at the cusp of the ongoing movement toward sustainable products, packaging, and processes. It is Techspray's intention to stay at the cutting-edge while keeping our products powerful and cost effective.



Chemical Properties

EXPOSURE LIMIT:	Limits on components not established. Manufacturer's recommendation 1000 ppm.
PHYSICAL STATE:	Liquid
ODOR:	Faint ethereal odor
APPEARANCE:	Clear, mobile liquid
pH:	5-6
PERCENT VOLATILE:	97% at 104°C
VAPOR PRESSURE:	< 0.01 mmHg@20°C (VOC Composite Vapor Pressure)
BOILING POINT :	~212°F (100°C)
FLASHPOINT AND METHOD (TAG Closed Cup):	None to boiling point 205°F (96°C) Note: does not sustain combustion.
SOLUBILITY IN WATER:	Fully miscible
DENSITY:	0.99 at 25°C
VOC (by wt.):	2.7%, 26.5 g/l
SHELF LIFE:	5 years unopened, 2 years opened

Chemical Component	CAS#
2-propanol-1-butoxy	5131-66-8
Alcohols, C6-C12, ethoxylated propoxylated	68937-66-6

Includes other hazardous components in non-reportable quantities.

Eco-Stencil™ SMT Stencil Cleaner Product# 1570

Usage Instructions

Manual Stencil Cleaning

- Spray and saturate area to be cleaned.
- Wipe gently at first to allow cleaning agent to break down paste or adhesive.
- Continue to wipe in a circular motion until remaining residues are fully removed.
- Replace wipe as it becomes overly saturated with the paste/adhesive or tattered.
- Dispose of soiled wipe appropriately depending on the type of paste/adhesive removed.

Underside Stencil Cleaning

- Fill cleaner into designated reservoir of SMT printer.
- Keep adequate liquid level.

Performance

Tested according to modified MIL-PRF-29608 4.59 standards: Paste dried for 5 minutes at 212°F (100°C). Paste is applied to cleaning coupons, sprayed with cleaning fluid, allowed to sit 10-seconds, then a poly-cellulose wipe (saturated with same cleaning fluid) is dragged across one time using a dowel to maintain consistent pressure. Percentage refers to the amount of soil (by weight) removed from stainless steel test coupon.

	Kester FL250D Lead, No-Clean	Kester HM531 Lead, Water-sol	Kester EM907 Lead-Free, No-Clean
Techspray Renew Eco-Stencil™ Cleaner 1570	53%	89%	34%
99.8% IPA	52%	53%	40%
Techspray™ Water-Based SMT Cleaner 1692	26%	not tested	not tested

Packaging and Availability

Eco-Stencil™ Cleaner available in the following sizes:

1570-100DSP	100 count pre-saturated wipes, 6" x 8" (15cm x 20cm)
1570-QT	1 quart (0.95L) w/trigger sprayer
1570-G	1 gallon (3.8L)

Available as special order, call for pricing:

1570-5G	5 gallon (19L)
1570-54G	54 gallon (205L)
1570-275G	275 gallon (1,045L)

Compatibility

Metals

Test method: 30 day submersion in sealed container.

Material	Compatibility
Brass foil	Excellent
Copper foil	Excellent
Nickel 200	Excellent
Aluminum 6061	Excellent
Aluminum 2024	Excellent
Anodized aluminum	Good ¹
Stainless Steel 316	Excellent
Stainless Steel 304	Excellent
Mild carbon steel	Not recommended ²
Galvanized Steel	Excellent

1 = Some paint traces removed.

2 = Heavy tarnish, rust, 0.02% material gain from oxidation and mineralization.

Note: Eco-Stencil™ is a water-based formula, so will encourage oxidation with prolonged exposure to iron, steel, and other susceptible metals.

Environmental Policy

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Resources

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.