



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



"High Frequency Ceramic Solutions"

1.575 & 1.602 GHz GPS/GLONASS SMD Chip Antenna

P/N 1575AT54A0010

Detail Specification: 1/15/2016

Page 1 of 8

General Specifications

Part Number	1575AT54A0010	Reel Quantity	500 pcs
Frequency (MHz)*	1575 - 1605 MHz	Operating Temperature	-40 to +85°C
Peak Gain (YZ-total)	1.3 dBi typ.	Storage Temperature	-40 to +85°C
Average Gain (YZ-total)	-0.7 dBi typ.	Recommended Storage Conditions of uninstalled product still on T&R	+5 ~ +35 °C, Humidity 45~75%RH
Return Loss	9.5 dB min.		
Impedance	50 Ω	Storage Period	18 months max.
Power Capacity	2W max. (CW)		


*Plus 5MHz of guard band on each side

Part Number Explanation

P/N Suffix	Packing Style	Bulk	Suffix = S	e.g.. 1575AT54A0010S
		T & R	Suffix = E	e.g.. 1575AT54A0010E
	Termination style	100% Tin	Suffix = E or S	e.g.. 1575AT54A0010(E or S)


Mechanical Dimensions

	In	mm
L	0.591 ± 0.008	15.00 ± 0.20
W	0.157 ± 0.008	4.00 ± 0.20
T	0.126 ± 0.008	3.20 ± 0.20
a	0.039 ± 0.008	1.00 ± 0.20
a1	0.020 ± 0.008	0.50 ± 0.20
b	0.020 ± 0.008	0.50 ± 0.20
c	0.236 ± 0.008	6.00 ± 0.20



Terminal Configuration

No.	Function
1	Feeding Point
2	GND
3	NC
4	GND



Want the layout file of this antenna for all the layout suggestions? Send us a message at: www.johansontechnology.com/ask-a-question

Let us assist you with the antenna design, layout and characterization, contact our RF Applications Team at: www.johansontechnology.com/ask-a-question

Johanson Technology, Inc. reserves the right to make design changes without notice. Please confirm the specifications and delivery conditions when placing your order. All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 1.7

2015 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"

1.575 & 1.602 GHz GPS/GLONASS SMD Chip Antenna

P/N 1575AT54A0010

Detail Specification: 1/15/2016

Page 2 of 8

GPS-only Mounting Considerations


EVB Johanson with SMA (orderable!)
reference p/n: 1575AT54A0010-EB1SMA and go to:
www.johansontechnology.com/component/samplerrequest

Want the layout file of this? Send us a message at:
www.johansontechnology.com/ask-a-question

****Note 2:** It is recommended that the designer leave available slots for a "pi" (or shunt-series-shunt) network. The antenna matching network values above are used when antenna is mounted on Johanson's evaluation board. The matching values on client's PCB will be different. Go to: <http://johansontechnology.com/tuning> and see how to obtain the new values. If you need further antenna assistance help, contact our RF Applications Eng Team at:


www.johansontechnology.com/ask-a-question

* Line width should be designed to match 50Ω characteristic impedance, depending on PCB material and thickness. Grounded CPWG will provide best results!



All units in mm

Johanson SMA test board-top view: Overall GND plane can be smaller, this is just for reference



All units in mm

Johanson Technology, Inc. reserves the right to make design changes without notice. Please confirm the specifications and delivery conditions when placing your order. All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 1.7

2015 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"

1.575 & 1.602 GHz GPS/GLONASS SMD Chip Antenna


P/N 1575AT54A0010

Detail Specification: 1/15/2016

Page 3 of 8

GPS-only Mounting Considerations


Johanson SMA test board-top view: Overall GND plane may be smaller, this is just for reference



Order this pre-tuned EVB! Limited to one per customer: www.johansontechnology.com/request-a-sample

Typical Electrical Characteristics for GPS only (T=25°C)

Return Loss / Without Matching Circuits



Johanson Technology, Inc. reserves the right to make design changes without notice. Please confirm the specifications and delivery conditions when placing your order. All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 1.7

2015 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"

1.575 & 1.602 GHz GPS/GLONASS SMD Chip Antenna

P/N 1575AT54A0010

Detail Specification: 1/15/2016

Page 4 of 8

GPS + GLONASS Mounting Considerations

* Line width should be designed to match 50Ω characteristic impedance, depending on PCB material and thickness.

EVB Johanson with SMA (orderable!)
reference p/n: 1575AT54A0010-EB2SMA and go to:
www.johansontechnology.com/component/samplerequest


****Note 2:** It is recommended that the designer leave available slots for a "pi" (or shunt-series-shunt) network. The antenna matching network values above are used when antenna is mounted on Johanson's evaluation board. The matching values on client's PCB will be different. Go to:
<http://johansontechnology.com/tuning> and see how to obtain the new values. If you need further help, contact our RF Applications Eng Team at:

www.johansontechnology.com/ask-a-question

Yellow area-
complete GND
and layer
clearance free of

*50 ohm
feedline


We use a 6.8nH
shunt, 1pF series,
and 6.8nH shunt
on our EVB, but**



All units in mm

Bottom view:

No ground area



Request layout file at: www.johansontechnology.com/ask-a-question Mention "GPS + GLONASS Mounting Considerations" layout file

All units in mm

Johanson Technology, Inc. reserves the right to make design changes without notice. Please confirm the specifications and delivery conditions when placing your order. All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 1.7

2015 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"

1.575 & 1.602 GHz GPS/GLONASS SMD Chip Antenna

P/N 1575AT54A0010

Detail Specification: 1/15/2016


Page 5 of 8

GPS + GLONASS Mounting Considerations

Want the layout file of this?
Send us a message at:

www.johansontechnology.com/ask-a-question

Johanson SMA test board-
top view: Overall GND
plane can be smaller, this
is just for reference




For GPS+GLNSS operation, please mount the antenna in the middle and at the edge of your PCB for optimum performance and enhanced bandwidth.

This EVB is for evaluation purposes and your design does not need to follow this layout exactly.

Order this pre-tuned EVB! Limited to one per customer: www.johansontechnology.com/request-a-sample

Typical Electrical Characteristics for GPS + GLONASS (T=25°C)

Return Loss / Without Matching Circuits



Johanson Technology, Inc. reserves the right to make design changes without notice. Please confirm the specifications and delivery conditions when placing your order. All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 1.7

2015 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"

1.575 & 1.602 GHz GPS/GLONASS SMD Chip Antenna







P/N 1575AT54A0010

Detail Specification: 1/15/2016

Page 6 of 8

GPS Typical Electrical Characteristics (T=25°C)

Typical Radiation Patterns



Johanson Technology, Inc. reserves the right to make design changes without notice. Please confirm the specifications and delivery conditions when placing your order. All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 1.7

2015 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"

1.575 & 1.602 GHz GPS/GLONASS SMD Chip Antenna







P/N 1575AT54A0010

Detail Specification: 1/15/2016

Page 7 of 8

GLNSS Typical Electrical Characteristics (T=25°C)

Typical Radiation Patterns: Vertical and Horizontal Cuts are added together in these plots



Johanson Technology, Inc. reserves the right to make design changes without notice. Please confirm the specifications and delivery conditions when placing your order. All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 1.7

2015 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"

1.575 & 1.602 GHz GPS/GLONASS SMD Chip Antenna

P/N 1575AT54A0010

Detail Specification: 1/15/2016

Page 8 of 8

Antenna layout review, tuning, and characterization services

www.johansontechnology.com/ipcantennaservices

More SMD Chip Antennas at:

www.johansontechnology.com/antennas

Soldering Information

www.johansontechnology.com/ipcsoldering-profile

Antenna layout and tuning techniques (How to obtain the new antenna matching values)

www.johansontechnology.com/tuning

Packaging information

www.johansontechnology.com/ipcpackaging.html

RoHS Compliance

www.johansontechnology.com/technical-notes/rohs-compliance.html

MSL Info

www.johansontechnology.com/technical-notes/msl-rating.html

P/N Explanation and Breakdown

www.johansontechnology.com/ipc-pn-explained

Johanson Technology, Inc. reserves the right to make design changes without notice. Please confirm the specifications and delivery conditions when placing your order. All sales are subject to Johanson Technology, Inc. terms and conditions.

Technical Author: Manuel Carmona



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 1.7

2015 Johanson Technology, Inc. All Rights Reserved