

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









General ordering data	
Order No.	1609050000
Part designation	ZTA 1/ZA
Version	Modular terminal, accessories, Test adapter
EAN	4008190206543
Qty.	25 pc(s).

## **Product notes**

Product description

The clip-on test adapter ZTA is used as a single thin element and as a test adapter strip for measurements in electrical cabinets. Conductors with cross-sections from 0.5 mm² to 1.5 mm² can be connected. The test adapter simply clips onto the terminal and thus guarantees reliable contact with the live busbar.

## Additional technical data

Installation advice Direct mounting

Conductors for clamping (rated connection)	
Clamping range, min.	0.5 mm <sup>2</sup>
Clamping range, max.	1.5 mm <sup>2</sup>
Type of connection	Plug-in connection
Stripping length	6 mm

Solid, min. 0.5 mm
Solid, max. 1.5 mm
Flexible, min. 0.5 mm
Flexible, max. 1.5 mm
Flexible with ferrule, min. (DIN 46228/1) 0.5 mm
Flexible with ferrule, max. (DIN 46228/1) 1.5 mm

Din		

Width	5.1 mm
Height of lowest version	73.1 mm
Length	31.5 mm



Dimensions	
Rating data	
Rated cross-section	1.5 mm <sup>2</sup>
Rated current	9 A
Test adapter	
Function	Test adapter
With snap-in pegs	Yes
Test adapter dimensions	
Height with TS 35	99.1 mm
With snap-in pegs	Yes
Test adapter rated data	
Rated voltage	250 V
Approvals	
Approvals institutes	PG
	ME25
Downloads	
STEP	1609050000_22247_ZTA_1_ZA_STP.stp
Classifications	
eClass 4.1	NK
eClass 5.0	NK
eClass 5.1	NK
Similar products	



Modular terminal, accessories, Test adapter

1609040000

ZTA 1