



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

## Device connector, front mounting - CA-17P1N126Y00 - 1619856

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Device connector for front wall, straight, shielded: yes, SPEEDCON locking, M23, Number of positions: 17, Type of contact: Male connector, Solder connection, Seal, axial

The figure shows the 12-pos. product version



### Key Commercial Data

|                      |          |
|----------------------|----------|
| Packing unit         | 1 pc     |
| Custom tariff number | 85366990 |
| Country of origin    | Germany  |

### Technical data

#### Temperature range

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 125 °C |
|---------------------------------|-------------------|

#### Data of the insulating body

|  |                      |
|--|----------------------|
| Coding   | N                    |
| Insulator material                             | PBT                  |
| Contact material                               | CuZn                 |
| Contact surface material                       | Ni/Au                |
| Contact connection method                      | Solder connection    |
| Type of contacts                               | Male connector       |
| Number of positions                            | 17                   |
| Contact diameter of power contacts             | 1 mm                 |
| Litz wire cross section of power contacts min. | 0.08 mm <sup>2</sup> |
| Litz wire cross section of power contacts max. | 1 mm <sup>2</sup>    |
| Nominal current per power contact at 25°C      | 8 A                  |
| Nominal voltage, power contact                 | 150 V                |
| Overvoltage category                           | II                   |

## Device connector, front mounting - CA-17P1N126Y00 - 1619856

### Technical data

#### Data of the insulating body

|                     |   |
|---------------------|---|
| Degree of pollution | 3 |
|---------------------|---|

#### Housing data

|  |                  |
|--|------------------|
| Housing material                       | CuZN             |
| Type of locking                        | SPEEDCON locking |
| Degree of protection (when plugged in) | IP67             |
| Thread type                            | M23              |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27143424 |
| eCl@ss 5.1 | 27143424 |
| eCl@ss 6.0 | 27143424 |
| eCl@ss 7.0 | 27440209 |
| eCl@ss 8.0 | 27440103 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002635 |
| ETIM 5.0 | EC002061 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 43172015 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11     | 43172015 |
| UNSPSC 12.01  | 43201404 |
| UNSPSC 13.2   | 43201404 |

### Approvals

#### Approvals

---

#### Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

---

## Device connector, front mounting - CA-17P1N126Y00 - 1619856

### Approvals

#### Ex Approvals

---

Approvals submitted

---

#### Approval details

| UL Recognized  |       |
|---|-------|
| mm <sup>2</sup> /AWG/kcmil  | 18    |
| Nominal current IN  | 8 A   |
| Nominal voltage UN  | 150 V |

| cUL Recognized  |       |
|--|-------|
| mm <sup>2</sup> /AWG/kcmil   | 18    |
| Nominal current IN   | 5 A   |
| Nominal voltage UN   | 150 V |


| EAC |
|-----|
|     |

| cULus Recognized  |
|--|
|  |


### Drawings

## Device connector, front mounting - CA-17P1N126Y00 - 1619856


Schematic diagram



Dimensional drawing



Dimensional drawing



Installation dimensions