imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Photovoltaic connector - PV-FT-CF-C-6-500-BK - 1621847

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



RoHS

Key Commercial Data

| Packing unit | 50 STK |
|------------------------|-----------------|
| Minimum order quantity | 50 STK |
| GTIN | 4 046356 988537 |
| GTIN | 4046356988537 |


Technical data

Environmental Product Compliance

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
| | No hazardous substances above threshold values |

Drawings

Dimensional drawing




a: anti-rotation protection

b: coding

c: panel thickness - plastic: 2 - 6 mm; metal: 2 - 5 mm

Dimensional drawing



Dimension x = cable length c: panel thickness - plastic: 2 - 6 mm; metal: 2 - 5 mm



Photovoltaic connector - PV-FT-CF-C-6-500-BK - 1621847

Approvals

Approvals

Approvals

EAC / TÜV Rheinland

Ex Approvals

Approval details

EAC

EAE

B.01742

| TÜV Rheinland | http://www.certipedia.com | R 60126961 |
|--------------------|---------------------------|------------|
| | | |
| Nominal voltage UN | 1500 V | |

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com