



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





#### General ordering data

Order No.	1632330000
Part designation	WTA 2/ZA WDU2.5-10
Version	Modular terminal, accessories, Test adapter
EAN	4008190257330
Qty.	25 pc(s).

#### Product notes

Note, technical data	Rated current 6 A
----------------------	-------------------

#### CSA rating data

Voltage (CSA)	300 V
CSA current	6 A

#### Conductors for clamping (additional connection)

Clamping range, max.	1.5 mm <sup>2</sup>
Rated cross-section	1.5 mm <sup>2</sup>
Clamping screw	M 2.5

#### Conductors for clamping (rated connection)

Type of connection	Screw connection
No. of connections	1
Stripping length	6 mm
Solid, min.	0.5 mm <sup>2</sup>
Solid, max.	1.5 mm <sup>2</sup>
Flexible, min.	1 mm <sup>2</sup>
Flexible, max.	1.5 mm <sup>2</sup>
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228/1)	1.5 mm <sup>2</sup>

#### Dimensions

Width	5 mm
Height of lowest version	107.6 mm
Length	66.1 mm

## Dimensions

### Rating data

Rated cross-section	1.5 mm <sup>2</sup>
Rated voltage	250 V
Rated current	6 A

### Stud connection

Tightening torque range	0.4 Nm
-------------------------	--------

### Test adapter

Function	Test adapter
With snap-in pegs	Yes

### Test adapter dimensions

Height with TS 35	107.6 mm
With snap-in pegs	Yes

### Test adapter rated data

Rated voltage	250 V
---------------	-------

### UL rating data

Voltage (UL)	300 V
Current (UL)	6 A

### Approvals

Approvals institutes



### Downloads

DXF	21837_WTA_2-ZA_WDU2.5-10_DXF.dxf
STEP	1632330000_21837_WTA_2_STP.stp

### Classifications

ETIM 2.0	NK
ETIM 3.0	EC002255
eClass 4.1	27-14-11-99
eClass 5.0	27-14-11-45
eClass 5.1	27-14-11-45

### Similar products

Order No.	Part designation	Version
1632320000	WTA 2 WDU2.5-10	Modular terminal, accessories, Test adapter
1632340000	WTA 2/10 WDU2.5/10	Modular terminal, accessories, Test adapter