

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







Order No. 1633210000 Part designation ZOS 2.5/3 Version Cross-connector / link for modular terminal, Cross-connection, No. of poles: 3 EAN 4008190263393 Qty. 20 pc(s).  Additional technical data Explosion-tested version "Ex e" No Installation advice Direct mounting  Cross-connector No. of cross-connected terminals 3 Pitch 12 mm Rated current, multi-pole 10 A Rated voltage 0 V Type Cross-connector Type of fixing Plugged Function Cross-connection No. of poles 3  Rating data Rated voltage 0 V Rated voltage 0 V Rated voltage 3 No. of poles 3  Rating data Rated voltage 0 V Rated current 24 A  Approvals Approvals institutes n.a.	General ordering data	
Version  Cross-connector / link for modular terminal, Cross-connection, No. of poles: 3  EAN  Qty.  Additional technical data  Explosion-tested version "Ex e" Installation advice  Direct mounting  Cross-connector  No. of cross-connected terminals Pitch 12 mm  Rated current, multi-pole Rated voltage 0 V Type Cross-connector  Type of fixing Plugged Function No. of poles  Rating data Rated voltage 0 V Rated current  Rated voltage 0 V Rated voltage Function No. of poles  Rated voltage 0 V Rated current  Rated voltage 0 V Rated current  Rated voltage 0 N Rating data Rated voltage 0 N Rated current  Approvals  Approvals  Approvals institutes		1633210000
Version  Cross-connector / link for modular terminal, Cross-connection, No. of poles: 3  EAN  Qty.  Additional technical data  Explosion-tested version "Ex e" Installation advice  Direct mounting  Cross-connector  No. of cross-connected terminals Pitch 12 mm  Rated current, multi-pole Rated voltage 0 V Type Cross-connector  Type of fixing Plugged Function No. of poles  Rating data Rated voltage 0 V Rated current  Rated voltage 0 V Rated voltage Function No. of poles  Rated voltage 0 V Rated current  Rated voltage 0 V Rated current  Rated voltage 0 N Rating data Rated voltage 0 N Rated current  Approvals  Approvals  Approvals institutes	Part designation	ZQS 2.5/3
Qty.     20 pc(s).       Additional technical data       Explosion-tested version "Ex e"     No       Installation advice     Direct mounting       Cross-connector     3       No. of cross-connected terminals     3       Pitch     12 mm       Rated current, multi-pole     10 A       Rated voltage     0 V       Type     Cross-connector       Type of fixing     Plugged       Function     Cross-connection       No. of poles     3       Rating data       Rated voltage     0 V       Rated current     24 A       Approvals       Approvals institutes     n.a.	Version	
Additional technical data  Explosion-tested version "Ex e" No Installation advice Direct mounting  Cross-connector  No. of cross-connected terminals 3 Pitch 12 mm Rated current, multi-pole 10 A Rated voltage 0 V Type Cross-connector Type of fixing Plugged Function Cross-connection No. of poles 3  Rating data Rated voltage 0 V Rated current 24 A  Approvals Approvals institutes n.a.	EAN	
Explosion-tested version "Ex e" No Installation advice Direct mounting  Cross-connector  No. of cross-connected terminals 3 Pitch 12 mm Rated current, multi-pole 10 A Rated voltage 0 V Type Cross-connector Type of fixing Plugged Function Cross-connection No. of poles 3  Rating data Rated voltage 0 V Rated current 24 A  Approvals Approvals institutes	Qty.	20 pc(s).
Installation advice  Cross-connector  No. of cross-connected terminals Pitch 12 mm Rated current, multi-pole Rated voltage 0 V Type Cross-connector Type of fixing Flugged Function No. of poles 3  Rating data Rated voltage 0 V Rated current  No. of poles  Rating data Rated voltage Approvals Approvals  Approvals  Approvals		
Cross-connector  No. of cross-connected terminals  Pitch 12 mm  Rated current, multi-pole 10 A  Rated voltage 0 V  Type Cross-connector  Type of fixing Plugged Function No. of poles 3  Rating data Rated voltage 0 V  Rated current  Approvals  Approvals  Approvals  Approvals  Approvals  And  Rated voltage Approvals  Approvals		
No. of cross-connected terminals  Pitch  Rated current, multi-pole  Rated voltage  Type  Cross-connector  Type of fixing  Function  No. of poles  Rating data  Rated voltage  O V  Rated current  O V  Rated voltage  Taking data  Rated voltage  Rated current  Approvals  Approvals  Approvals institutes	Installation advice	Direct mounting
Pitch 12 mm Rated current, multi-pole 10 A Rated voltage 0 V Type Cross-connector Type of fixing Plugged Function Cross-connection No. of poles 3  Rating data Rated voltage 0 V Rated current 24 A  Approvals Approvals institutes   12 mm 10 A	Cross-connector	
Rated current, multi-pole 10 A Rated voltage 0 V Type Cross-connector Type of fixing Plugged Function Cross-connection No. of poles 3  Rating data Rated voltage 0 V Rated current 24 A  Approvals Approvals institutes   10 A  0 V  Cross-connector  V Cross-connection  0 V  Rating data  Rated voltage 0 V  Rated current 24 A	No. of cross-connected terminals	3
Rated voltage Type Cross-connector Type of fixing Plugged Function Cross-connection No. of poles 3  Rating data Rated voltage 0 V Rated current 24 A  Approvals Approvals institutes	Pitch	12 mm
Type of fixing Plugged Function Cross-connection No. of poles 3  Rating data Rated voltage 0 V Rated current 24 A  Approvals Approvals institutes	Rated current, multi-pole	10 A
Type of fixing Plugged Function Cross-connection No. of poles 3  Rating data Rated voltage 0 V Rated current 24 A  Approvals Approvals institutes	Rated voltage	0 V
Function Cross-connection No. of poles 3  Rating data Rated voltage 0 V Rated current 24 A  Approvals Approvals institutes	Туре	Cross-connector
No. of poles 3  Rating data Rated voltage 0 V Rated current 24 A  Approvals Approvals institutes	Type of fixing	Plugged
Rating data Rated voltage 0 V Rated current 24 A  Approvals Approvals institutes	Function	Cross-connection
Rated voltage 0 V Rated current 24 A  Approvals Approvals institutes	No. of poles	3
Rated voltage 0 V Rated current 24 A  Approvals Approvals institutes	Rating data	
Approvals Approvals institutes  n.a.		0 V
Approvals institutes n.a.		24 A
Approvals institutes n.a.	Approvals	
Classifications		n.a.
	Classifications	
eClass 4.1 27-14-11-99		27-14-11-99
eClass 5.0 27-14-11-40	eClass 5.0	27-14-11-40
eClass 5.1 27-14-11-40		

## Similar products

Order No		
Order No.		
1633200000	ZQS 2.5/2	Cross-connector / link for modular terminal, Cross-connection, No. of poles: 2
1633220000	ZQS 2.5/4	Cross-connector / link for modular terminal, Cross-connection, No. of poles: 4
1633230000	ZQS 2.5/5	Cross-connector / link for modular terminal, Cross-connection, No. of poles: 5

