imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





IFM Magnifiers 16345LG Old item no.: 16345LG

LUXO

IFM1A 3D 3C LIGHT GRAY/GRIS

IFM is an ideal lighter-duty magnifier for low-power inspection. A 22W circline fluorescent lamp provides 360° shadow-free illumination and a lamp diffuser cover protects the bulb from damage. 3-diopter (1.75X) lens. 45" external spring-balanced arm. Edge clamp mount. Color: light grey.





Lightsource

| - | |
|------------------------------|---------|
| Number of lamps | 1 |
| Lamp power (W) | 2 2 |
| Lamp base | G 1 0 Q |
| CRI and/or Color Temperature | 4100K |
| Lightsource | Т 9 |
| | |

Optic

| Color of reflector | White |
|-----------------------|-------|
| Material of reflector | PC |
| Working distance (mm) | 333 |
| Magnification (X) | 1.75 |

Body

| Body material | Steel |
|---------------|-------|
| Body color | Grey |

| Electrical data | |
|------------------------|-----------------|
| Maximum frequency (Hz) | 6 0 |
| Minimum frequency (Hz) | 5 0 |
| Maximum voltage (V) | 120 |
| Voltage from (V) | 100 |
| Dimensions | |
| Net weight (kg) | 0 |
| Gross weight (lb.) | 9 |
| Arm length (in.) | 4 5 |
| Termination | |
| Cord length (ft) | 6 |
| Mounting | Edge clamp |
| Ballast | |
| Type of Pallact | Electromagnetic |

Type of Ballast

Electromagnetic