

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Cable gland - HC-M-KV-M25(14-21) - 1646007

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Metal screw connection up to 5 bar, thread length: 7 mm, cable diameter: 14 - 21 mm, WAF 34, screw connection: M25



Key Commercial Data

| Packing unit | 25 STK |
|--------------|-----------------|
| GTIN | 4 017918 941277 |
| GTIN | 4017918941277 |

Technical data

Dimensions

| Length | 37 mm |
|---------------------------------|-----------------|
| Wrench size, union nut | 34 mm |
| Wrench size, support | 34 mm |
| Hexagon angular dimension | 36 mm |
| Length of the connecting thread | 7 mm |
| Feed-through hole diameter | 25.1 mm 25.2 mm |
| External cable diameter | 14 mm 21 mm |

Ambient conditions

| Degree of protection | IP68 (up to 5 bar) |
|---------------------------------|--------------------|
| Ambient temperature (operation) | -30 °C 100 °C |

General

| No. of conductors | 1 |
|-----------------------------|---------------------|
| Cable gland material | Nickel-plated brass |
| Material, insert | PA |
| Cable seal material | CR/NBR |
| Shielded | no |
| Thread type connection side | M25 x 1.5 |



Cable gland - HC-M-KV-M25(14-21) - 1646007

Technical data

General

| Torque | 10 Nm (Union nut) |
|--------|------------------------|
| | 10 Nm (Support sleeve) |
| Color | silver |

Standards and Regulations


| Halogen-free | no |
|--------------|----|
|--------------|----|

Environmental Product Compliance

| REACh SVHC | Lead 7439-92-1 |
|------------|---|
| China RoHS | Environmentally Friendly Use Period = 50 |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Drawings

Dimensional drawing



Dimensional drawing

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com