



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



HC-B 32-SD-FQU/FS


Order No.: 1646120



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1646120>

HEAVYCON protective cover, type B32, for supporting base element with double locking latch, with retaining cord, IP54, PA

Commercial data

GTIN (EAN)	 4 017918 927301
sales group	D093
Pack	10 pcs.
Customs tariff	39269097
Catalog page information	Page 550 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
03/01/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data



General data

Design	B32
Type	For supporting base element with double locking latch
Locking type	For double locking latch
Degree of protection	IP54
Ambient temperature (operation)	-20 °C ... 100 °C

Material, protective cover	PA
Inflammability class acc. to UL 94	HB
Connection	Plastic protective cover for short-term protection

Diagrams/Drawings

Dimensioned drawing



Protective cover, B32

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;