



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





#### General ordering data

Order No.	1652000000
Part designation	ZIA 1.5/3L-PE
Version	Initiator/actuator terminal, 1.5 mm <sup>2</sup> , Tension clamp connection, Wemid, green, TS 35
EAN	4008190401658
Qty.	20 pc(s).

#### Product notes

Note, ordering data	ZVL 1.5 O.QV = distribution strip without internal bridge for park position
Note, technical data	Bi-directional LED in ZIA 1.5/3L-1/LD (1651990000)
Product description	The modular distribution strip system

#### Additional technical data

Colour of insulating material	green
Connection direction	top
End plate required	Yes
Explosion-tested version "Ex e"	No
Installation advice	TS 35
Insulating material	Wemid
Levels cross-connected internally	No
No. of levels	1
Open sides	right
Operating temperature range	- 50 °C, + 120 °C
Product family	Z-series
Type of connection	Tension clamp connection
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V-0
Version	ZIK-ZAK-System

#### CSA rating data

Voltage (CSA)	300 V
CSA current	10 A

#### CSA rating data

Min. cross-section (CSA)	AWG 26
Max. cross-section (CSA)	AWG 14

#### Conductors for clamping (additional connection)

Flexible with ferrule, min. (DIN 46228 pt 1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228 pt 1)	1.5 mm <sup>2</sup>

#### Conductors for clamping (rated connection)

Clamping range, min.	0.13 mm <sup>2</sup>
Clamping range, max.	2.5 mm <sup>2</sup>
Type of connection	Tension clamp connection
Connection direction	top
No. of connections	2
Stripping length	8 mm
Blade size	0.6 x 3.5 mm
Gauge to IEC 60947-1	A1
Solid, min.	0.5 mm <sup>2</sup>
Solid, max.	2.5 mm <sup>2</sup>
Flexible, min.	0.5 mm <sup>2</sup>
Flexible, max.	2.5 mm <sup>2</sup>
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228/1)	1.5 mm <sup>2</sup>
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0.5 mm <sup>2</sup>
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	1.5 mm <sup>2</sup>
Twin wire-end ferrule, min.	0.5 mm <sup>2</sup>
Twin wire end ferrule, max.	0.75 mm <sup>2</sup>
AWG conductor size, min.	AWG 26
AWG conductor size, max.	AWG 14

#### Dimensions

Width	5.08 mm
Height of lowest version	46 mm
Length	68.5 mm
TS 35 offset	32.5 mm

#### Rating data

Rated cross-section	1.5 mm <sup>2</sup>
Rated voltage	250 V
Rated impulse voltage	4 kV
Rated current	17.5 A
Standards	IEC 60947-7-1
Pollution severity	3

#### UL rating data

Voltage (UL)	300 V
Current (UL)	10 A
Min. cross-section (UL)	AWG 26
Max. cross-section (UL)	AWG 14

#### UL rating data

#### Approvals

Approvals institutes



#### Downloads

STEP 1652000000\_22244\_ZIA\_1.5-3L-PE\_STP.stp

#### Classifications

eClass 4.1	27-14-11-28
eClass 5.0	27-14-11-28
eClass 5.1	27-14-11-28

#### Similar products

Order No.	Part designation	Version
1651980000	ZIA 1.5/3L-1S	Initiator/actuator terminal, 1.5 mm <sup>2</sup> , Tension clamp connection, Wemid, dark beige, TS 35
1651990000	ZIA 1.5/3L-1S/LD	Initiator/actuator terminal, 1.5 mm <sup>2</sup> , Tension clamp connection, Wemid, dark beige, TS 35