



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## FO connecting cable - VS-PC-2XHCS-200-SCRJ/FSMA-2 - 1654976

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Assembled fiber optic cable, break-out cable, HCS fiber 200/230  $\mu\text{m}$ , SCRJ/IP20 on FSMA/IP20, for installation inside control cabinets, length: 2 m



### Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	91.0 GRM
Custom tariff number	85369010
Country of origin	Germany

### Technical data

#### Mechanical characteristics

Number of positions	2
Connection profile	SCRJ according to DIN EN 50377-6-1
Fiber	200/230 $\mu\text{m}$
Number of fibers	2.00
Insertion/withdrawal cycles	$\geq 1000$
Type of cable	Break-out cable
Length of cable	2 m

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 70 °C
Degree of protection	IP20

#### Material data

Housing material	PBT/nickel silver
Outer sheath, material	TPE-O
External sheath, color	orange

# FO connecting cable - VS-PC-2XHCS-200-SCRJ/FSMA-2 - 1654976

## Technical data

### Material data

Ferrule holder color	Red
----------------------	-----

## Classifications

### eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27061003
eCl@ss 7.0	27061003
eCl@ss 8.0	27061003

### ETIM


ETIM 2.0	EC000764
ETIM 3.0	EC001263
ETIM 4.0	EC001263
ETIM 5.0	EC000830

### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501


## Drawings

Schematic diagram



Pin assignment plug SCRJ


Dimensioned drawing



SCRJ connector IP20

# FO connecting cable - VS-PC-2XHCS-200-SCRJ/FSMA-2 - 1654976

Dimensioned drawing



FSMA plugs