



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



VS-ST-KX-75-LP


Order No.: 1655645



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1655645>

Coaxial contact, for D-SUB combination inserts, for PCB assembly,
pin, angled, gold-plated

Commercial data

| | |
|--------------------------|--|
| GTIN (EAN) |  4 046356 029537 |
| Note | Made-to-order |
| sales group | D502 |
| Pack | 10 pcs. |
| Customs tariff | 85369010 |
| Catalog page information | Page 325 (PC-2009) |

Product notes

WEEE/RoHS-compliant since:
09/07/2006



[http://
www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)
Please note that the data given
here has been taken from the
online catalog. For comprehensive
information and data, please refer
to the user documentation. The
General Terms and Conditions of
Use apply to Internet downloads.

Technical data

Mechanical characteristics

| | |
|-----------------------------|-------|
| Insertion/withdrawal cycles | ≥ 500 |
|-----------------------------|-------|

| | |
|-------------------------------------|-------------------|
| Type of connection | PCB mounting |
| Insertion force per signal contact | ≤ 7.00 N |
| Extraction force per signal contact | ≤ 7 N |
| Ambient temperature (operation) | -55 °C ... 135 °C |

Material data

| | |
|--------------------------|------------------------------|
| Contact material | Copper alloy |
| Contact surface material | Hard gold-plated over nickel |

Electrical characteristics

| | |
|-----------------------|-------|
| Rated voltage (III/3) | 250 V |
| Rated current | 2 A |
| Insulation resistance | 10 TΩ |

Accessories

| Item | Designation | Description |
|--------------|----------------|---|
| Tools | | |
| 1676747 | HC-M4-KOAX-EWZ | Contact removal tool for coaxial contacts |

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;