

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









## RJ45 sleeve housings - VS-08-T-H-RJ45/IP67-BK - 1658671

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)



RJ45 sleeve housing, IP67, for pin insert VS-08-ST-H11-RJ45 and VS-08-ST-H21-RJ45, with push-pull interlocking for panel mounting frames, for cable cross section 5.0 mm ... 8.5 mm, color: black



### Ethernet

## Key commercial data

| Packing unit                         | 11        |
|--------------------------------------|-----------|
| Minimum order quantity               | 5 1       |
| Weight per Piece (excluding packing) | 14.14 GRM |
| Custom tariff number                 | 85366990  |
| Country of origin                    | Germany   |

## Technical data

#### Mechanical characteristics

| Insertion/withdrawal cycles | ≥ 1000      |
|-----------------------------|-------------|
| External cable diameter     | 5 mm 8.5 mm |
| Cable exit                  | Straight    |
| Color                       | black       |

#### Ambient conditions

| Ambient temperature (operation) | -40 °C 80 °C |
|---------------------------------|--------------|
| Degree of protection            | IP67         |

### Material data

| Inflammability class according to UL 94 | V0  |
|---|-----|
| Housing material                        | PA  |
| Material, O-ring                        | FPM |
| Cable seal material                     | NBR |



## RJ45 sleeve housings - VS-08-T-H-RJ45/IP67-BK - 1658671

## Classifications

### eCl@ss

| eCl@ss 4.0 | 272607xx |
|------------|----------|
| eCl@ss 4.1 | 27260701 |
| eCI@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27261203 |
| eCl@ss 7.0 | 27440202 |
| eCl@ss 8.0 | 27440202 |

#### **ETIM**

| ETIM 3.0 | EC000437 |
|----------|----------|
| ETIM 4.0 | EC000437 |
| ETIM 5.0 | EC000437 |

### UNSPSC

| UNSPSC 6.01   | 31261501 |
|---------------|----------|
| UNSPSC 7.0901 | 31261501 |
| UNSPSC 11     | 31261501 |
| UNSPSC 12.01  | 31261501 |
| UNSPSC 13.2   | 31261501 |

#### Accessories

Accessories

Male insert

RJ45 male insert - VS-08-ST-H11-RJ45 - 1652716



RJ45 pin insert, CAT5e, 8-pos., shielded, IDC connection method, for litz wires AWG 27 ... 26, with strain relief

#### RJ45 male insert - VS-08-ST-H21-RJ45 - 1652729




RJ45 male insert, CAT6, 8-pos., shielded, IDC displacement connection, for litz wire AWG 25 ... 24 and solid wires AWG 24, with strain relief



# RJ45 sleeve housings - VS-08-T-H-RJ45/IP67-BK - 1658671

## Drawings

#### Dimensioned drawing



RJ45 sleeve housing IP67

© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com