



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



3M™ Fire Block Sealant FB 136

3M ID SGBGBCSD1044



Details

- Easy clean up with water
- Thixotropic (will not sag or run in vertical or overhead applications)
- Halogen-free
- Tack-free in approximately 15 minutes
- Applied with standard caulking gun or trowel (high caulk rate)

A versatile, one component, water-based, non-combustible draft, smoke and fireblocking sealant, designed to resist high temperatures and smoke passage in non-rated construction. Meets ASTM E 136 noncombustibility requirements. Gray color, no mixing required.

Product can be installed with a standard caulking gun or it can be easily applied with a putty knife or trowel. 3M™ Fire Block Sealant FB 136 will bond to concrete, brick, metals, wood, plastic, and cable jacketing. 3M™ Fire Block Sealant FB 136 meets current International Building Code (IBC), International Residential Code (IRC), International Residential Mechanical Code, International Fuel Gas Code and NFPA 5000 draft, smoke and fireblocking requirements.

Suggested Applications

- Typical applications include: sealing interior construction voids around wires, pipes, HVAC ducts and vents, in wood or steel framed non-rated construction. May also be used around chimney, fireplace and other framing gaps. Not for exterior use.