imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



HDC enclosures HDC 24B SBU 1PG21G



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Туре	HDC 24B SBU 1PG21G			
Order No.	<u>1661510000</u>			
Version	HDC enclosures, Size: 8, Protection degree: IP 65, Base enclosure, Side-locking clamp on lower side,			
	Standard, Size of cable entries: PG 21			
GTIN (EAN)	4008190418069			
Qty.	1 pc(s).			

HDC enclosures HDC 24B SBU 1PG21G

Technical data

Dimensions and weights



Weidmüller Interface GmbH & Co. KG


Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Size 8 Design Standard Top partottom part/lid lower part Design of locking system Side-locking of lower side Cable entry w. threading Number of cable entries PG 2 1 Number of cable entry on top 0 Number of cable entries PG 2 1 Number of cable entry on top 0 Number of cable entry sideways 1 Classifications ETIM 2.0 EC000437 ETIM 3.0 EC000437 UNSPSC 30-21-18-01 eClass 4.1 40-02-06-14 eClass 5.1 27-14-34-19 eClass 6.2 27-26-12-03 eClass 7.1 27-44-02-02 eClass 6.2 27-26-12-03 Approvals Conform Downloads PDF 1661510000_HDC_24B_SBU_1PG216_STP_Blatt_1.pdf IGES 1661510000_HDC_24B_SBU_1PG216_STP_Blatt_1.pdf Iggs Iggs Iggs	Dimensions and weights					
Height 64 mm Mounting dimension - width 132 mm Mounting dimension - height 45 mm Net weight 421 g Dimensions Total length housing 120 mm Width housing B 64 mm Height of base C1 57.5 mm Height of housing B 64 mm Total length housing 120 mm Width housing C 43 mm Width base C1 57.5 mm Height of housing B 64 mm Cable entry w. threading 132 mm Hole pitch length A2 132 mm General data diecast aluminium Version Version Stae enclosu Internal thread PG 21 Design of housing Base enclosu Size 8 Design of locking system Sidelocking of lower side Cable entry w. threading Size of cable entry is dieways 1 Number of cable entry on top 0 Number of cable entry sideways 1 Class f.1 27-14-34-19 eClass 6.2 27-26-12-03 eClass f.1 27-14-402-02 Approvals eClass 6.2 27-26-12-03 ROHS Conform Downloads PDF 1661510000 HDC -24B SBU 1PG216. STP Blatt _ 1.pdf	Lenath	163 mm	Width	57.5 mm		
Mounting dimension - height 45 mm Net weight 421 g Dimensions Total length housing 120 mm Width housing C 43 mm Height of base B1 5 mm Height of housing B 64 mm Height of base B1 5 mm Hole pitch length A2 132 mm Cable entry w. threading Housing main material diecast aluminium Version Internal thread PG 21 Design of housing Base enclosu Size 8 Design of locking system Side-locking i lower side Cable entry w. threading Size of cable entries PG 21 Number of cable entry on top 0 Number of cable entry sideways 1 Class fileations ETIM 3.0 EC000437 ETIM 3.0 EC000437 ETIM 2.0 EC000437 ETIM 3.0 EC000437 eclass 5.1 27.14.34.19 eclass 6.2 27.26.12.03 eclass 7.1 27.44.02.02 A002.06.14 eclass 6.2 27.26.12.03 Approvals Site Conform Eco00437 ETIM 3.0 Eco00437 PDF 1661510000_HDC_24B_SBU_1PG216_STP_Blatt_1.pdf 1665 1661510000_HDC_24B_SBU_1PG216_STP_Blatt_1.pdf		64 mm	Mounting dimension - width			
Total length housing 120 mm Width housing C 43 mm Width base C1 57.5 mm Height of housing B 64 mm Height of housing B 64 mm Height of housing C 132 mm Cable entry w. threading Hole pitch length A2 132 mm General data diccast aluminium Version Internal thread PG 21 Internal thread PG 21 Design of housing Base enclosu Size 8 Design of locking system Side-locking Cable entry w. threading Design of locking system Side-locking Number of cable entry on top 0 Number of cable entries PG 21 UNSPSC 30-21-18-01 eClass 6.2 27-26-12-03 eClass 5.1 27-14-34-19 eClass 6.2 27-26-12-03 eClass 5.1 27-24-02.02 Approvals Approvals		45 mm		421 g		
Width base C1 57.5 mm Height of housing B 64 mm Height of base B1 5 mm Hole pitch length A2 132 mm Cable entry w. threading Idecast aluminium Idecast aluminium Version Internal thread PG 21 Design of housing Base enclosu Size 8 Design of housing Base enclosu Top partottom part/lid lower part Side-locking of locking system Side-locking of lower side Cable entry w. threading Size of cable entries PG 21 Number of cable entry on top 0 Number of cable entry sideways 1 Classifications ETIM 3.0 EC000437 ETIM 3.0 EC000437 ETIM 2.0 EC000437 ETIM 3.0 EC000437 UNSPSC 30-21-18-01 eClass 6.2 27-26-12-03 eClass 7.1 27-44-02-02 Approvals Approvals	Dimensions					
Width base C1 57.5 mm Height of housing B 64 mm Height of base B1 5 mm Hole pitch length A2 132 mm Cable entry w. threading Idecast aluminium Idecast aluminium Version Internal thread PG 21 Design of housing Base enclosu Size 8 Design of housing Base enclosu Top partottom part/lid lower part Side-locking of locking system Side-locking of lower side Cable entry w. threading Size of cable entries PG 21 Number of cable entry on top 0 Number of cable entry sideways 1 Classifications ETIM 3.0 EC000437 ETIM 3.0 EC000437 ETIM 2.0 EC000437 ETIM 3.0 EC000437 UNSPSC 30-21-18-01 eClass 6.2 27-26-12-03 eClass 7.1 27-44-02-02 Approvals Approvals						
Height of base B1 5 mm Hole pitch length A2 132 mm Cable entry w. threading General data General data diecast aluminium Version Version Design of housing Base enclosu Internal thread PG 21 Design of housing Base enclosu Size 8 Design of locking system Side-locking of lower side Cable entry w. threading Diver part Design of locking system Side-locking of lower side Cable entry w. threading Size of cable entries PG 21 Number of cable entry sideways 1 Classifications ETIM 2.0 EC000437 ETIM 3.0 EC000437 ETIM 2.0 EC000437 eClass 4.1 40-02-06-14 eClass 5.1 27-14-34-19 eClass 6.2 27-26-12-03 eClass 7.1 27-44-02-02 Approvals EConform EConform Approvals Conform EConform EConform EConform Downloads E055 1661510000_HDC_248_SBU_1PG216_STP_Blatt_1.pdf Efficient 1.pdf	Total length housing	120 mm		43 mm		
Cable entry w. threading General data Housing main material diecast aluminium Version Internal thread PG 21 Size 7 B B Base enclosu Design of housing Base enclosu Design of housing Base enclosu Design of housing Design of housing Base enclosu Design of housing Design of housing Base enclosu Design of housing Design of housing Base enclosu Design of housing Design of housing Base enclosu Design of housing Base enclosu Design of housing Base enclosu Design of housing Design of housing Base enclosu Design of housing Base enclosu Design of housing Design of housing Base enclosu Design of housing Base enclosu Design of housing Design of housing Base enclosu Design of housing Base enclosu Design of locking system Side-locking of Design of locking system Side-locking of Design of cloking system Side-locking of Design of	Width base C1	57.5 mm	Height of housing B	64 mm		
General data Housing main material diecast aluminium Version Internal thread PG 21 Size 8 Design of housing Base enclosu Top partotom part/lid Iower part Design of locking system Sidelocking a Cable entry w. threading Number of cable entry sideways 1 Classifications ETIM 2.0 EC000437 ETIM 3.0 EC000437 UNSPSC 30-21-18-01 eClass 4.1 40-02-06-14 eClass 7.1 27-44-02-02 eClass 6.2 27-26-12-03 Approvals Conform ETIM 3.0 EC000437 POF 1661510000 HDC 24B_SBU_1PG21G_STP_Blatt_1.pdf 1.pdf IGES 1661510000 HDC 24B_SBU_1PG21G_STP_Blatt_1.pdf		5 mm	Hole pitch length A2	132 mm		
Housing main material diecast aluminium Version Internal thread PG 21 Size 8 Top partottom part/lid lower part Cable entry w. threading Number of cable entry on top 0 Classifications ETIM 2.0 EC000437 ETIM 2.0 EC000437 UNSPSC 30-21-18-01 eClass 5.1 27-14-34-19 eClass 5.1 27-14-34-19 eClass 5.1 27-27-26-12-03 ETIM 3.0 EC000437 eClass 6.2 27-26-12-03 EC000437 eClass 6.2 EC000437 EC000437 eClass 6.2 EC000437 EC000437 EC0000 E	Cable entry	w. threading				
Version Internal thread PG 21 Size 8 Top partottom part/lid lower part Loble entry w. threading Number of cable entry on top 0 Number of cable entry on top 0 Classifications ETIM 2.0 ETIM 2.0 EC000437 UNSPSC 30-21-18-01 eClass 5.1 27-14-34-19 eClass 7.1 27-44-02-02 Approvals ETIM 3.0 EC000437 eClass 6.2 27-26-12-03 Base End base End base Approvals Conform End base PDF 16615100000_HDC_24B_SBU_1PG216_STP_Blatt_1.pdf IGES 1661510000_HDC_24B_SBU_1PG216_STP_Blatt_1.pdf	General data					
Internal thread PG 21 Size 8 Top partottom part/lid lower part Cable entry w. threading 0 Number of cable entry on top 0 Classifications ETIM 2.0 EC000437 UNSPSC 30-21-18-01 eClass 4.1 40-02-06-14 eClass 5.1 27-14-34-19 eClass 6.2 27-26-12-03 eClass 7.1 27-44-02-02 Approvals Approvals ROHS Conform Downloads PDF 1661510000 HDC 24B SBU 1PG21G STP. Blatt_ 1.pdf IGES 16000 HDC 24B SBU 1PG21G STP. Blatt_ 1.pdf IGES 16000 HDC 24B SBU 1PG21G STP. Blatt_ 1.pdf	Housing main material	diecast aluminium				
Size 8 Top partottom part/lid Iower part Cable entry w. threading Number of cable entry on top 0 Classifications Size of cable entries ETIM 2.0 EC000437 UNSPSC 30-21-18-01 eClass 5.1 27-14-34-19 eClass 6.2 27-26-12-03 eClass 7.1 27-44-02-02 Approvals ROHS Conform Downloads PDF 1661510000_HDC_24B_SBU_1PG216_STP_Blatt1.pdf IGES 1661510000_HDC_24B_SBU_1PG216_STP_Blatt1.pdf IGES	Version					
Size 8 Top partottom part/lid Iower part Cable entry w. threading Number of cable entry on top 0 Classifications Size of cable entries ETIM 2.0 EC000437 UNSPSC 30-21-18-01 eClass 5.1 27-14-34-19 eClass 6.2 27-26-12-03 eClass 7.1 27-44-02-02 Approvals ROHS Conform Downloads PDF 1661510000_HDC_24B_SBU_1PG216_STP_Blatt1.pdf IGES 1661510000_HDC_24B_SBU_1PG216_STP_Blatt1.pdf IGES						
Top partottom part//lid Jower part Side-locking of locking system Side-locking of lower side Cable entry w. threading Size of cable entries PG 21 Number of cable entry on top 0 Number of cable entry sideways 1 Classifications ETIM 2.0 EC000437 ETIM 3.0 EC000437 UNSPSC 30-21-18-01 eClass 4.1 40-02-06-14 eClass 5.1 27-14-34-19 eClass 6.2 27-26-12-03 Approvals Approvals ROHS Conform Downloads PDF 1661510000_HDC_24B_SBU_1PG21G_STP_Blatt_1.pdf IGES 1661510000_HDC_24B_SBU_1PG21G_STP_Blatt_1.pdf				Base enclosure		
Iower part Iower side Cable entry w. threading Size of cable entries PG 21 Number of cable entry on top 0 Number of cable entry sideways 1 Classifications ETIM 2.0 EC000437 ETIM 3.0 EC000437 UNSPSC 30-21-18-01 eClass 4.1 40-02-06-14 eClass 5.1 27-14-34-19 eClass 6.2 27-26-12-03 eClass 7.1 27-44-02-02 Approvals Conform	-	8				
Number of cable entry on top 0 Number of cable entry sideways 1 Classifications Classifications ETIM 2.0 EC000437 ETIM 3.0 EC000437 UNSPSC 30-21-18-01 eClass 4.1 40-02-06-14 eClass 5.1 27-26-12-03 eClass 7.1 27-44-02-02 27-26-12-03 27-26-12-03 27-26-12-03 Approvals Conform Conform Conform ETIM Supervises Conform PDF 1661510000 HDC 24B SBU 1PG216 STP Blatt 1.pdf 1661510000 HDC 24B SBU 1PG216 STP Blatt 1.pdf 1661510000 HDC 24B SBU 1PG216 STP Blatt 1.pdf	Top partottom part/lid	lower part	Design of locking system	Side-locking clamp or lower side		
Classifications ETIM 2.0 EC000437 UNSPSC 30-21-18-01 eClass 5.1 27-14-34-19 eClass 5.1 27-26-12-03 eClass 7.1 27-26-12-03 Approvals Approvals Conform Downloads PDF 1661510000 HDC 24B SBU 1PG21G STP Blatt_1.pdf IGES	Cable entry	w. threading	Size of cable entries	PG 21		
ETIM 2.0 EC000437 EC000437 UNSPSC 30-21-18-01 eClass 4.1 40-02-06-14 eClass 5.1 27-14-34-19 eClass 6.2 27-26-12-03 eClass 6.2 27-26-12-03 Approvals Approvals ROHS Conform Downloads PDF 1661510000 HDC 24B SBU 1PG216 STP Blatt 1.pdf IGES 1661510000 HDC 24B SBU 1PG216 STP Blatt 1.pdf	Number of cable entry on top	0	Number of cable entry sideways	1		
UNSPSC 30-21-18-01 eClass 4.1 40-02-06-14 eClass 5.1 27-14-34-19 eClass 6.2 27-26-12-03 eClass 7.1 27-44-02-02 Approvals Conform Approvals Conform Conform Downloads 1661510000_HDC_248_SBU_1PG21G_STP_Blatt_1.pdf 1.pdf IGES 1661510000_HDC_248_SBU_1PG21G_STP_igs 1.pdf	Classifications					
UNSPSC 30-21-18-01 eClass 4.1 40-02-06-14 eClass 5.1 27-14-34-19 eClass 6.2 27-26-12-03 eClass 7.1 27-44-02-02 eClass 6.2 27-26-12-03 Approvals Conform Conform eClass 6.2 27-26-12-03 ROHS Conform Conform eClass 6.2 27-26-12-03 PDF 1661510000 HDC 24B_SBU_1PG21G_STP_Blatt_1.pdf 1661510000 HDC 24B_SBU_1PG21G_STP_ligs		50000407	FT 114.0.0	50000407		
eClass 5.1 27-14-34-19 eClass 6.2 27-26-12-03 eClass 7.1 27-44-02-02 Approvals Approvals Approvals Conform Conform Downloads 1661510000_HDC_248_SBU_1PG216_STP_Blatt_1.pdf 1gEs						
eClass 7.1 27-44-02-02 Approvals Approvals Conform Conform Downloads PDF 1661510000_HDC_24B_SBU_1PG216_STP_Blatt_1.pdf 1661510000_HDC_24B_SBU_1PG216_STP_Blatt_1.pdf 1661510000_HDC_24B_SBU_1PG216_STP.gas						
Approvals Image: Conform ROHS Conform Downloads 1661510000_HDC_248_SBU_1PG216_STP_Blatt_1.pdf IGES 1661510000_HDC_248_SBU_1PG216_STP_Blatt_1.pdf	-		eClass 6.2	27-26-12-03		
Approvals Conform Conform Conform Downloads PDF 1661510000_HDC_24B_SBU_1PG21G_STP_Blatt_1.pdf IGES 1661510000_HDC_24B_SBU_1PG21G_STP.igs	eClass 7.1	27-44-02-02				
ROHS Conform Downloads PDF 1661510000_HDC_24B_SBU_1PG21G_STP_Blatt_1.pdf IGES 1661510000_HDC_24B_SBU_1PG21G_STP.igs	Approvals					
Image: Conform Downloads PDF 1661510000_HDC_24B_SBU_1PG21G_STP_Blatt_1.pdf IGES 1661510000_HDC_24B_SBU_1PG21G_STP.igs	Approvals					
Image: Conform Downloads PDF 1661510000_HDC_24B_SBU_1PG21G_STP_Blatt_1.pdf IGES 1661510000_HDC_24B_SBU_1PG21G_STP.igs						
Downloads PDF 1661510000_HDC_24B_SBU_1PG21G_STP_Blatt1.pdf IGES 1661510000_HDC_24B_SBU_1PG21G_STP.igs			09			
PDF 1661510000_HDC_24B_SBU_1PG21G_STP_Blatt1.pdf IGES 1661510000_HDC_24B_SBU_1PG21G_STP.igs	ROHS	Conform				
IGES <u>1661510000_HDC_24B_SBU_1PG21G_STP.igs</u>	Downloads					
IGES <u>1661510000_HDC_24B_SBU_1PG21G_STP.igs</u>	PDF	1661510000 HDC 24B SBU 1PG21G STP Blatt 1 pdf				
	VRML	<u>1661510000 HDC_24B_SBU_1PG21G_STP.wrl</u>				
		1661510000.MZF				

<u>3-D model</u>

HDC enclosures HDC 24B SBU 1PG21G

Drawings





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com