



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



CK4,0-ED-2,50BU AG

Order No.: 1663284

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1663284>Turned 4.0 crimp contact, individual female contact, core diameter
2.50 mm², silver-plated**Commercial data**

GTIN (EAN)	 4 017918 123093
sales group	D090
Pack	25 pcs.
Customs tariff	85366990
Catalog page information	Page 529 (PC-2009)

Product notesWEEE/RoHS-compliant since:
10/30/2006

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**Electrical characteristics**

Note	For HC-M-3 modules
Volume resistance	≤ 0.003 Ω
Ambient temperature (operation)	-40 °C ... 125 °C

Mechanical characteristics

Conductor cross-section	2.5 mm ²
Connection cross-section AWG	14
Stripping length of the individual wire	9 mm (9.6 mm (4-6 mm ²))
Insertion/withdrawal cycles	≥ 500

General characteristics

Type	Individual female contact
Series	HC-M-03

Material data

Contact material	Copper alloy
Contact surface material	hard-silver plated

Certificates / Approvals



Certification GOST, UL

Accessories


Item	Designation	Description
------	-------------	-------------

Tools


1662735	CK4,0-EWZ	Contact removal tool, for rotated CK-4,0-... contacts
1205846	CRIMPFOX-4,0-ED-2,50	Crimping pliers, for CK 4.0... contacts, for conductor cross sections 1.5 - 2.5 mm ²
1205859	CRIMPFOX-4,0-ED-6,00	Crimping pliers, for CK 4.0... contacts, for conductor cross sections 3.0 - 6.0 mm ²

Diagrams/Drawings

Diagram



Dimensioned drawing



Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;