

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Housing - HC-B 16-TFL-45/O1PG21G - 1673782

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)

Sleeve housing, for single locking latch, height 45 mm, without screw connection, 1x Pg21, straight cable entry





Key commercial data

| Packing unit | 1 PCE |
|--------------------------------------|------------|
| Weight per Piece (excluding packing) | 167.31 GRM |
| Custom tariff number | 85389099 |
| Country of origin | Germany |

Technical data

Dimensions

| Height | 45 mm |
|--------|-------|
| Width | 43 mm |
| Length | 94 mm |

Ambient conditions

| Degree of protection of housing (IP) | IP65 |
|--------------------------------------|---------------|
| Ambient temperature (operation) | -40 °C 125 °C |

General

| Note | For contact inserts HC-B16, BB32, D40, DD72, HS6, M, K |
|------------------------------|--|
| Design | B16 |
| Housing type | Sleeve housings |
| Locking type | for single locking latch |
| No. of cable exits | 1 |
| Cable exit | Straight |
| Screw connection | None |
| Type of the screw connection | 1x Pg21 |



Housing - HC-B 16-TFL-45/O1PG21G - 1673782

Technical data

General

| Housing material | Aluminum die-cast |
|--------------------------|---------------------|
| Housing surface material | Powder-coated, gray |

Classifications

eCl@ss

| eCl@ss 4.0 | 27140816 |
|------------|----------|
| eCl@ss 4.1 | 27140816 |
| eCl@ss 5.0 | 27143424 |
| eCl@ss 5.1 | 27143424 |
| eCl@ss 6.0 | 27143424 |
| eCl@ss 7.0 | 27440209 |
| eCl@ss 8.0 | 27440209 |

ETIM

| ETIM 2.0 | EC000437 |
|----------|----------|
| ETIM 3.0 | EC000437 |
| ETIM 4.0 | EC000437 |
| ETIM 5.0 | EC000437 |

UNSPSC

| UNSPSC 6.01 | 31261502 |
|---------------|----------|
| UNSPSC 7.0901 | 31261502 |
| UNSPSC 11 | 31261502 |
| UNSPSC 12.01 | 31261502 |
| UNSPSC 13.2 | 31261502 |

Approvals

Approvals

Approvals

GOST

Ex Approvals



Housing - HC-B 16-TFL-45/O1PG21G - 1673782


Approvals

Approvals submitted

Approval details



Drawings



© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com